

Sika® Separol GU ZA

Oil based shutter release agent

Product Description

Sika® Separol GU ZA is an oil based release agent formulated to provide easy release properties to formwork and a high quality surface finish.

Uses

Sika® Separol GU ZA, when applied to steel, plastic or timber formwork allows clean, fast and easy striking.

Characteristics / Advantages

Sika® Separol GU ZA provides the following beneficial properties:

- Suitable for use on wood, metals and plastic
- Allows clean, easy striking
- Improved finish for fair faced concrete
- Reduces concrete contamination
- Economical coverage rates

Tests

Approval/Standards

Product Data

Form

Appearance/Colours	Liquid	Brownish yellow
---------------------------	--------	-----------------

Packaging	25 and 200 litre drums.
------------------	-------------------------

Storage

Storage Conditions / Shelf-Life

12 months from date of production if stored properly in original unopened, undamaged, sealed packaging. Protect from frost, direct sunlight and contamination. Opened units should be stored closed.

Technical Data

Chemical Base	Oil based agent
----------------------	-----------------

Density	0,85 kg/litre
----------------	---------------

Layer Thickness	Thin layer
------------------------	------------



System Information

Application Details

Consumption/Dosage

Timber :

- approx. 25 sq. meters per litre depending on porosity.

Steel or plastic:

- approx. 50 sq. meters per litre depending on surface texture and porosity.

Application Conditions / Limitations

Ambient Temperature

Min.5°C - Max.35°C

Application Instructions

Notes on Application / Limits

Do not dilute
Protect from rain until dry.

Local Restrictions

Please note that as a result of specific local regulations the performances of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

Health and Safety Information

Protective Measures

Contact with skin and eyes must be avoided.

Ecology

Transportation Class

Important Notes

Residues of material must be removed according to local regulations. Fully cured material can be disposed of as household waste under agreement with the responsible local authorities.

Detailed health and safety information as well as detailed precautionary measures e.g. physical, toxicological and ecological data can be obtained from the Material Safety Data Sheet.

Toxicity

Legal Notes

The information, and, in particular, the recommendations relating to the application and end-use of Sika® products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the Product Data Sheet for the product concerned, copies of which will be supplied on request or accessed on the Internet under www.sika.co.za.



Sika South Africa (Pty) Ltd
9 Hocking Place,
Westmead, 3608
South Africa

E-Mail: headoffice@za.sika.com
Phone +27 31 792 6500
Telefax +27 31 700 1760
www.sika.co.za

