

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikafloor 161 Comp. B

Revision Date 06.03.2020

Version 1.0

Print Date 06.03.2020

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Sikafloor 161 Comp. B

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Epoxy coating, Product is not intended for consumer use

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika South Africa (Pty) Ltd  
9 Hocking Place  
Westmead  
3608 Pinetown  
South Africa  
Telephone : +27 (0)31 792 6500  
Telefax : +27 (0)31 700 1760  
E-mail address of person responsible for the SDS : headoffice@za.sika.com

#### 1.4 Emergency telephone number

+27 82 490 9409

### SECTION 2: Hazards identification

Type of product : Mixture

#### 2.1 Classification of the substance or mixture

##### Classification (SANS 10234)

Acute toxicity, Category 4	H302: Harmful if swallowed.
Skin corrosion, Sub-category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (SANS 10234)

Hazard pictograms :



Signal word : Danger

Hazard statements : H302 Harmful if swallowed.  
H314 Causes severe skin burns and eye damage.

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikafloor 161 Comp. B

Revision Date 06.03.2020

Version 1.0

Print Date 06.03.2020

	H317	May cause an allergic skin reaction.
	H412	Harmful to aquatic life with long lasting effects.
Supplemental Hazard Statements	: EUH071	Corrosive to the respiratory tract.
Precautionary statements	: <b>Prevention:</b>	
	P261	Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
	<b>Response:</b>	
	P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
	P304 + P340 + P310	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.
	P305 + P351 + P338 + P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

Hazardous components which must be listed on the label:

Adduct IXA-P (epoxy amine adduct, polymer)  
3-aminomethyl-3,5,5-trimethylcyclohexylamine  
m-phenylenebis(methylamine)  
2,4,6-tris(dimethylaminomethyl)phenol

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (SANS 10234)	Concentration (% w/w)
benzyl alcohol	100-51-6 202-859-9 01-2119492630-38-XXXX	Acute Tox.4; H302 Acute Tox.4; H332 Eye Irrit.2; H319	>= 40 - < 60

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikafloor 161 Comp. B

Revision Date 06.03.2020

Version 1.0

Print Date 06.03.2020

Adduct IXA-P (epoxy amine adduct, polymer)	212580-83-1	Acute Tox.4; H302 Skin Sens.1; H317 Aquatic Chronic3; H412	>= 20 - < 25
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2 220-666-8 01-2119514687-32-XXXX	Acute Tox.4; H302 Acute Tox.4; H312 Skin Corr.1B; H314 Skin Sens.1A; H317 Aquatic Chronic3; H412 Eye Dam.1; H318	>= 10 - < 20
m-phenylenebis(methylamine)	1477-55-0 216-032-5 01-2119480150-50-XXXX	Acute Tox.4; H302 Acute Tox.4; H332 Skin Corr.1B; H314 Skin Sens.1; H317 Aquatic Chronic3; H412	>= 10 - < 20
Hydrocarbons, C9, aromatics	Not Assigned 265-199-0 01-2119455851-35-XXXX [corresponding group CAS 64742-95-6]	Flam. Liq.3; H226 STOT SE3; H336 STOT SE3; H335 Asp. Tox.1; H304 Aquatic Chronic2; H411	>= 5 - < 10
2,4,6-tris(dimethylaminomethyl)phenol Contains: bis[(dimethylamino)methyl]phenol <= 15 %	90-72-2 202-013-9 01-2119560597-27-XXXX	Skin Sens.1B; H317 Skin Corr.1C; H314 Eye Dam.1; H318	>= 3 - < 5

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikafloor 161 Comp. B

Revision Date 06.03.2020

Version 1.0

Print Date 06.03.2020

---

- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Keep eye wide open while rinsing.
- If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Gastrointestinal discomfort  
Allergic reactions  
Dermatitis  
See Section 11 for more detailed information on health effects and symptoms.
- Risks : Health injuries may be delayed.  
corrosive effects  
sensitising effects  
Harmful if swallowed.  
May cause an allergic skin reaction.  
Causes serious eye damage.  
Corrosive to the respiratory tract.  
Causes severe burns.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.
- 

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

### 5.2 Special hazards arising from the substance or mixture

- Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikafloor 161 Comp. B

Revision Date 06.03.2020

Version 1.0

Print Date 06.03.2020

---

Further information : Standard procedure for chemical fires.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Deny access to unprotected persons.

#### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For personal protection see section 8.

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

---

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikafloor 161 Comp. B

Revision Date 06.03.2020

Version 1.0

Print Date 06.03.2020

Fire-fighting class : 3

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re-sealed and kept upright to prevent leakage. Store in accordance with local regulations.

Other data : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

---

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166  
Eye wash bottle with pure water  
Wear eye/face protection.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

Suitable for short time use or protection against splashes:  
Butyl rubber/nitrile rubber gloves (0,4 mm)  
Contaminated gloves should be removed.  
Suitable for permanent exposure:  
Viton gloves (0.4 mm),  
breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
organic vapor filter (Type A)  
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikafloor 161 Comp. B

Revision Date 06.03.2020

Version 1.0

Print Date 06.03.2020

Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: light yellow
Odour	: amine-like
Odour Threshold	: No data available
Flash point	: ca. 68 °C
Autoignition temperature	: No data available
Decomposition temperature	: No data available
Lower explosion limit (Vol-%)	: No data available
Upper explosion limit (Vol-%)	: No data available
Flammability	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
pH	: ca. 11 at 20 °C
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: No data available
Vapour pressure	: 19,9983 hPa
Density	: ca. 1,03 g/cm <sup>3</sup> at 20 °C
Water solubility	: insoluble
Partition coefficient: n-octanol/water	: No data available

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikafloor 161 Comp. B

Revision Date 06.03.2020

Version 1.0

Print Date 06.03.2020

---

Viscosity, dynamic	:	ca.100 mPa.s at 20 °C
Viscosity, kinematic	:	> 20,5 mm <sup>2</sup> /s at 40 °C
Relative vapour density	:	No data available
Evaporation rate	:	No data available

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

### 10.4 Conditions to avoid

Conditions to avoid : No data available

### 10.5 Incompatible materials

Materials to avoid : No data available

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Harmful if swallowed.

#### Components:

##### benzyl alcohol:

Acute oral toxicity : LD50 Oral (Rat): 1.620 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4,178 mg/l  
Exposure time: 4 h

---



# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikafloor 161 Comp. B

Revision Date 06.03.2020

Version 1.0

Print Date 06.03.2020

Test atmosphere: dust/mist

### **Adduct IXA-P (epoxy amine adduct, polymer):**

Acute oral toxicity : LD50 Oral (Rat): 500 mg/kg

### **3-aminomethyl-3,5,5-trimethylcyclohexylamine:**

Acute oral toxicity : LD50 Oral (Rat): 1.030 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,01 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

### **m-phenylenebis(methylamine):**

Acute oral toxicity : LD50 Oral (Rat): 930 mg/kg

Acute inhalation toxicity : LC50 (Rat): 1,34 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rat): > 3.100 mg/kg

### **Hydrocarbons, C9, aromatics:**

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

### **2,4,6-tris(dimethylaminomethyl)phenol:**

Acute oral toxicity : LD50 Oral (Rat): 2.169 mg/kg

### **Skin corrosion/irritation**

Causes severe burns.

### **Serious eye damage/eye irritation**

Causes serious eye damage.

### **Respiratory or skin sensitisation**

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

### **Germ cell mutagenicity**

Not classified based on available information.

### **Carcinogenicity**

Not classified based on available information.

### **Reproductive toxicity**

Not classified based on available information.

### **STOT - single exposure**

Corrosive to the respiratory tract.

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikafloor 161 Comp. B

Revision Date 06.03.2020

Version 1.0

Print Date 06.03.2020

### **STOT - repeated exposure**

Not classified based on available information.

### **Aspiration toxicity**

Not classified based on available information.

---

## **SECTION 12: Ecological information**

### **12.1 Toxicity**

#### **Components:**

##### **benzyl alcohol:**

Toxicity to fish : LC50 (Fish): > 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
aquatic invertebrates Exposure time: 48 h

##### **3-aminomethyl-3,5,5-trimethylcyclohexylamine:**

Toxicity to algae : ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100 mg/l  
Exposure time: 72 h

##### **m-phenylenebis(methylamine):**

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): > 10 - 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l  
aquatic invertebrates Exposure time: 48 h

##### **Hydrocarbons, C9, aromatics:**

Toxicity to algae : (Pseudokirchneriella subcapitata (green algae)): 2,6 - 2,9 mg/l  
Exposure time: 72 h

##### **2,4,6-tris(dimethylaminomethyl)phenol:**

Toxicity to algae : EC50 (Scenedesmus capricornutum (fresh water algae)): > 10 - 100 mg/l  
Exposure time: 72 h

### **12.2 Persistence and degradability**

No data available

### **12.3 Bioaccumulative potential**

No data available

### **12.4 Mobility in soil**

No data available

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikafloor 161 Comp. B

Revision Date 06.03.2020

Version 1.0

Print Date 06.03.2020

---

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Other adverse effects

**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.  
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.  
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

European Waste Catalogue : 08 01 11\* waste paint and varnish containing organic solvents or other dangerous substances

Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated by dangerous substances

---

## SECTION 14: Transport information

### 14.1 UN number

ADR : UN 1760  
IMDG : UN 1760  
IATA : UN 1760

---

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikafloor 161 Comp. B

Revision Date 06.03.2020

Version 1.0

Print Date 06.03.2020

### 14.2 UN proper shipping name

<b>ADR</b>	:	CORROSIVE LIQUID, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-phenylenebis(methylamine))
<b>IMDG</b>	:	CORROSIVE LIQUID, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-phenylenebis(methylamine))
<b>IATA</b>	:	Corrosive liquid, n.o.s. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-phenylenebis(methylamine))

### 14.3 Transport hazard class(es)

<b>ADR</b>	:	8
<b>IMDG</b>	:	8
<b>IATA</b>	:	8

### 14.4 Packing group

<b>ADR</b>		
Packing group	:	II
Classification Code	:	C9
Hazard Identification Number	:	80
Labels	:	8
Tunnel restriction code	:	(E)
<b>IMDG</b>		
Packing group	:	II
Labels	:	8
EmS Code	:	F-A, S-B
Alkalis		
<b>IATA</b>		
Packing instruction (cargo aircraft)	:	855
Packing instruction (passenger aircraft)	:	851
Packing instruction (LQ)	:	Y840
Packing group	:	II
Labels	:	Corrosive

### 14.5 Environmental hazards

<b>ADR</b>		
Environmentally hazardous	:	no
<b>IMDG</b>		
Marine pollutant	:	no

### 14.6 Special precautions for user

No data available

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikafloor 161 Comp. B

Revision Date 06.03.2020

Version 1.0

Print Date 06.03.2020

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (= > 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH Information: All substances contained in our Products are  
- registered by our upstream suppliers, and/or  
- registered by us, and/or  
- excluded from the regulation, and/or  
- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams), (d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)  
Volatile organic compounds (VOC) content: 50,65 %

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 50,65 %

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikafloor 161 Comp. B

Revision Date 06.03.2020

Version 1.0

Print Date 06.03.2020

### SECTION 16: Other information

#### Full text of H-Statements

H226	: Flammable liquid and vapour.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H314	: Causes severe skin burns and eye damage.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

#### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Skin Corr.	: Skin corrosion
Skin Sens.	: Skin sensitisation
STOT SE	: Specific target organ toxicity - single exposure
ADR	: European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	: Chemical Abstracts Service
DNEL	: Derived no-effect level
EC50	: Half maximal effective concentration
GHS	: Half maximal effective concentration
IATA	: International Air Transport Association
IMDG	: International Maritime Code for Dangerous Goods
LD50	: Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	: Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	: International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	: Occupational Exposure Limit
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikafloor 161 Comp. B

Revision Date 06.03.2020

Version 1.0

Print Date 06.03.2020

---

SVHC : Substances of Very High Concern  
vPvB : Very persistent and very bioaccumulative

### Classification of the mixture:

Acute Tox. 4	H302
Skin Corr. 1B	H314
Eye Dam. 1	H318
Skin Sens. 1	H317
Aquatic Chronic 3	H412

### Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

ZA / EN