

## PRODUCT DATA SHEET

## Sarnacol®-2142 S

Adhesive for Sikaplan® and Sarnafil® felt backed roof waterproofing membranes

**DESCRIPTION**

Sarnacol®-2142 S is a 1-part, polyurethane based moisture curing adhesive

**USES**

Bonding Sarnafil® Sikaplan® type membranes to roof substrates.

**Bonding substrates**

- PIR insulation boards: glass, mineral fibre fleece or aluminium facing
- EPS insulation boards
- Concrete, lightweight concrete, plaster
- Oriented fibre strand boards, plywood panels
- Bitumen membranes (slated/sanded)
- Sandwich panels
- Metal sheet

**CHARACTERISTICS / ADVANTAGES**

- Proven performance over decades.
- Adheres to solid, rough, clean, dry or slightly moist surfaces
- Application by roller
- Good adhesion to different substrates

**APPROVALS / STANDARDS**

- Factory Mutual (FM) Certificate

**PRODUCT INFORMATION**

Chemical Base	Polyurethane moisture curing	
Packaging	One way container	15 kg
	Packing unit	Euro pallet or single container
	Refer to current price list for packaging variations	
Shelf Life	12 months from date of production.	
Storage Conditions	The product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +30 °C. Always refer to packaging.	
Density	~1,00 kg/l (+20 °C)	
Volatile organic compound (VOC) content	VOC-CH	18,8 %
	VOC-EU	18,8 %
Consistency	Liquid	

## APPLICATION INFORMATION

Consumption	Substrate	Consumption (g/m <sup>2</sup> )
	Timber, Metal, Sandwich Panel	250 - 350
	EPS: slab stock foaming cut	250
	PIR (glass tissue facing, aluminium facing)	250 - 350
	Mineral-fibre board (glass tissue facing)	300 - 350
	Bituminous sheet (sanded / slated)	300 - 400
Consumption depends on the roughness and absorbency of the substrate. Recommended consumption of Sarnacol®-2142 S on different substrates (+20 °C / 50 % r.h. ) These figures are theoretical and do not allow for any additional material due to surface porosity, surface profile, variations in level or wastage etc.		
Ambient Air Temperature	+5 °C min	
Substrate Temperature	+5 °C min	

## SYSTEM INFORMATION

Compatibility	<b>Incompatible substrates:</b> <ul style="list-style-type: none"><li>▪ Single ply waterproofing membranes without a felt backing</li><li>▪ Talcum coated bituminous sheets</li><li>▪ EPS in case of consumption &gt;300 g/m<sup>2</sup></li></ul>
---------------	--

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## FURTHER DOCUMENTS

- Installation instructions: Sarnafil® TG 76 or Sikaplan® SGK system fully bonded for exposed roofs.

## LIMITATIONS

- The use of some ancillary products such as adhesives, cleaners and solvents is limited to temperatures above +5 °C. Observe temperature limitations in the appropriate Product Data Sheets.
- Special measures may be compulsory for installation below +5 °C ambient temperature due to safety requirements in accordance with national regulations.

## ECOLOGY HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

## APPLICATION INSTRUCTIONS

### SUBSTRATE QUALITY

The substrate must offer sufficient strength and adhesion to resist the forces generated by wind suction.

### SUBSTRATE PREPARATION

The substrate must be firm, clean, dry or slightly moist, free from oil, grease, dust, stripping agents, standing water, bitumen residue and loose friable particles.

## APPLICATION

Strictly follow installation procedures as defined in method statements, application manuals and working instructions which must always be adjusted to the actual site conditions.

### General information

Sarnacol®-2142 S must be stirred carefully before use. Keep adhesive container closed whenever adhesive is not being used to prevent surface skinning.

To improve the workability of the adhesive at low temperatures, the closed container can be placed in warm water (max. +40 °C).

Adhesive residue on Sikaplan® SGK must be cleaned with SikaRoof® Cleaner L-100. Adhesive residue on Sarnafil® T Felt, must be cleaned with Sarnafil® T Clean.

### General bonding procedure - Wet bonding

The adhesive is spread evenly onto the substrate by using a synthetic application roller directly from the container and ensuring there are no lumps in the applied layers.

### Bonding Membranes

Apply adhesive onto the substrate. Do not apply the adhesive to an area greater than can be covered within 15 minutes. Do not pour out the adhesive and roll in a second stage. Once the adhesive surface has become 'tacky', apply the membrane onto the adhesive. Press down firmly on the membrane using a suitable pressure roller such as a water-filled, or heavy steel roller 40 – 50 kg.

## CLEANING OF TOOLS

Clean all tools and application equipment with Sarnafil® T Clean immediately after use. Hardened material can only be mechanically removed.

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### Sika South Africa (Pty) Ltd

9 Hocking Place,  
Westmead, 3608  
South Africa  
Phone +27 31 792 6500  
www.sika.co.za



### Product Data Sheet

Sarnacol®-2142 S  
May 2025, Version 06.01  
020945072000000005

Sarnacol-2142S-en-ZA-(05-2025)-6-1.pdf