According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Everbuild Maximum Torque

Revision Date 29.01.2021 Version 1.0 Print Date 29.01.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Everbuild Maximum Torque

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika South Africa (Pty) Ltd

9 Hocking Place Westmead 3608 Pinetown South Africa

Telephone : +27 (0)31 792 6500
Telefax : +27 (0)31 700 1760
E-mail address of person : headoffice@za.sika.com

responsible for the SDS

1.4 Emergency telephone number

+27 82 490 9409

SECTION 2: Hazards identification

Type of product : Mixture

2.1 Classification of the substance or mixture

Classification (SANS 10234)

Skin sensitisation, Category 1 Long-term (chronic) aquatic hazard, Cat-

egory 3

H317: May cause an allergic skin reaction.

H412: Harmful to aquatic life with long lasting ef-

fects.

2.2 Label elements

Labelling (SANS 10234)

Hazard pictograms :

Maning

Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting ef-

fects.

Precautionary statements : P101 If medical advice is needed, have product

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Everbuild Maximum Torque

Revision Date 29.01.2021 Version 1.0 Print Date 29.01.2021

container or label at hand.

P102 Keep out of reach of children.

Prevention:

P261 Avoid breathing dust/ fume/ gas/ mist/ va-

pours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves.

Disposal:

P501 Dispose of contents/container in accord-

ance with local regulation.

Hazardous components which must be listed on the label:

N-(3-(trimethoxysilyl)propyl)ethylenediamine

Pentamethyl piperidylsebacate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.	(SANS 10234)	(% w/w)
	Registration number		
trimethoxyvinylsilane	2768-02-7	Flam. Liq.3; H226	>= 2,5 - < 5
Contains:	220-449-8	Acute Tox.4; H332	
tetramethyl orthosilicate <= 0,2 %	01-2119513215-52-		
	XXXX		
N-(3-	1760-24-3	Eye Dam.1; H318	< 1
(trimethoxysi-	217-164-6	Skin Sens.1B;	
lyl)propyl)ethylenediamine	01-2119970215-39-	H317	
Contains:	XXXX	STOT SE3; H335	
N,N'-bis[3-			
(trimethoxysi-			
lyl)propyl]ethylenediamine <= 3 %			
1-(2-Aminoethyl)-2,2-dimethoxy-1-			
aza-2-silacyclopentane <= 3 %			
Pentamethyl piperidylsebacate	1065336-91-5	Skin Sens.1A;	>= 0,25 - < 1
Contains:		H317	
bis(1,2,2,6,6-pentamethyl-4-piperidyl)	01-2119491304-40-	Aquatic Acute1;	
sebacate	XXXX	H400	
methyl 1,2,2,6,6-pentamethyl-4-		Aquatic Chronic1;	
piperidyl sebacate		H410	

For explanation of abbreviations see section 16.

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Everbuild Maximum Torque

Version 1.0 Print Date 29.01.2021 Revision Date 29.01.2021

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

> Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Allergic reactions

See Section 11 for more detailed information on health effects

and symptoms.

Risks : sensitising effects

May cause an allergic skin reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

In case of fire, use water/water spray/water jet/carbon diox-Suitable extinguishing media

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod- : No hazardous combustion products are known

ucts

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Everbuild Maximum Torque

Revision Date 29.01.2021 Version 1.0 Print Date 29.01.2021

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Do not breathe vapours or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Everbuild Maximum Torque

Revision Date 29.01.2021 Version 1.0 Print Date 29.01.2021

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated

place. Store in accordance with local regulations.

Further information on stor-

age stability

: No decomposition if stored and applied as directed.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis	
methanol	67-56-1	TWA	200 ppm	2006/15/EC	
			260 mg/m3		
	Further information: Indicative, Identifies the possibility of significant uptake				
	through the skin				
		TWA OEL-RL	200 ppm	ZA OEL	
			260 mg/m3		
	Further information: Absorption through the skin, Recommended Limit				
		STEL OEL-RL	250 ppm	ZA OEL	
			310 mg/m3		

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Everbuild Maximum Torque

Revision Date 29.01.2021 Version 1.0 Print Date 29.01.2021

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : No special measures required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : paste
Colour : white, black
Odour : slight

Odour Threshold : No data available

pH : Not applicable substance/mixture is non-soluble (in water)

Melting point/range / Freezing :

point

No data available

Boiling point/boiling range : No data available

Flash point : > 61 °C

Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : 0,01 hPa

Relative vapour density : No data available

Density : ca. 1,32 g/cm3 (20 $^{\circ}$ C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Everbuild Maximum Torque

Revision Date 29.01.2021 Version 1.0 Print Date 29.01.2021

Viscosity, dynamic : ca. 500.000 mPa.s (20 °C)

Viscosity, kinematic : > 20,5 mm2/s (40 °C)

Explosive properties : No data available

Oxidizing properties : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

Hazardous decomposition : methanol

products

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

trimethoxyvinylsilane:

Acute oral toxicity : LD50 Oral (Rat): ca. 7.120 mg/kg

Acute inhalation toxicity : LC50: ca. 16,8 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Everbuild Maximum Torque

Revision Date 29.01.2021 Version 1.0 Print Date 29.01.2021

Acute dermal toxicity : LD50: 3.540 mg/kg

N-(3-(trimethoxysilyl)propyl)ethylenediamine:

Acute oral toxicity : LD50 Oral (Rat): 2.995 mg/kg

Pentamethyl piperidylsebacate:

Acute oral toxicity : LD50 Oral (Rat): 3.230 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Pentamethyl piperidylsebacate:

Toxicity to fish : LC50 (Fish): 0,97 mg/l

: 1

Exposure time: 96 h

M-Factor (Short-term (acute)

aquatic hazard)

M-Factor (Long-term (chron- : 1

ic) aquatic hazard)

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Everbuild Maximum Torque

Revision Date 29.01.2021 Version 1.0 Print Date 29.01.2021

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Other adverse effects

Product:

Additional ecological infor-

mation

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated

by dangerous substances

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Everbuild Maximum Torque

Revision Date 29.01.2021 Version 1.0 Print Date 29.01.2021

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mix-

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)

Conditions of restriction for the following entries should be considered: Number on list 3

1.2-Benzenedicarboxvlic acid. di-C9-11-branched alkyl esters, C10-rich (Number on list 52)

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).

REACH - List of substances subject to authorisation

(Annex XIV)

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals **REACH Information:** All substances contained in our Products are

None of the components are listed

(=> 0.1 %).

Not applicable

: Not applicable

Not applicable

Not applicable Not applicable

Country ZA 100000005182

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Everbuild Maximum Torque

Revision Date 29.01.2021 Version 1.0 Print Date 29.01.2021

- registered by our upstream suppliers, and/or

- registered by us, and/or

excluded from the regulation, and/orexempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV)

Volatile organic compounds (VOC) content: 0,06 %

no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 0,06 %

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapour.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.

H332 : Harmful if inhaled.

H335 : May cause respiratory irritation.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam.: Serious eye damageFlam. Liq.: Flammable liquidsSkin Sens.: Skin sensitisation

STOT SE : Specific target organ toxicity - single exposure

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Everbuild Maximum Torque

Revision Date 29.01.2021 Version 1.0 Print Date 29.01.2021

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Classification of the mixture: Classification procedure:

Skin Sens. 1 H317 Calculation method Aquatic Chronic 3 H412 Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

ZA / EN