According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



# Sikafloor 304/305 W Part B

Revision Date 24.03.2021 Version 1.1 Print Date 24.03.2021

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikafloor 304/305 W Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Flooring system, For professional users only.

1.3 Details of the supplier of the safety data sheet

Company name of supplier Sika South Africa (Pty) Ltd

> 9 Hocking Place Westmead 3608 Pinetown South Africa

+27 (0)31 792 6500 Telephone +27 (0)31 700 1760 Telefax E-mail address of person headoffice@za.sika.com responsible for the SDS

1.4 Emergency telephone number

+27 82 490 9409

### **SECTION 2: Hazards identification**

Type of product : Mixture

### 2.1 Classification of the substance or mixture

### Classification (SANS 10234)

Acute toxicity, Category 4 H332: Harmful if inhaled.

Serious eye damage, Category 1 H318: Causes serious eve damage. Skin sensitisation, Category 1 H317: May cause an allergic skin reaction. Specific target organ toxicity - single ex-H335: May cause respiratory irritation.

posure, Category 3, Respiratory system Long-term (chronic) aquatic hazard, Cat-H412: Harmful to aquatic life with long lasting ef-

egory 3

#### 2.2 Label elements

## Labelling (SANS 10234)

Hazard pictograms



fects.

Signal word Danger

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



# Sikafloor 304/305 W Part B

Revision Date 24.03.2021	Version	1.1	Print Date 24.03.2021
Hazard statements :	H317	May cause an allerg	gic skin reaction.
	H318	Causes serious eye	
	H332	Harmful if inhaled.	· ·
	H335	May cause respirate	ory irritation.
	H412		ife with long lasting ef-
Precautionary statements :	Prevention:		
,	P261	Avoid breathing dus pours/ spray.	st/ fume/ gas/ mist/ va-
	P273	Avoid release to the	e environment.
	P280	Wear protective gloperotection.	ves/ eye protection/ face
	Response:		
	-	air and keep comfor	Remove person to fresh rtable for breathing. Call R/ doctor if you feel un-
	P305 + P351 + P	with water for sever	
	P333 + P313	If skin irritation or ra	sh occurs: Get medical

Hazardous components which must be listed on the label:

Hexamethylene-1,6-diisocyanate homopolymer

Poly(oxy-1,2-ethanediyl), .alpha.-tridecyl-.omega.-hydroxy-, phosphate

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

advice/ attention.

# **SECTION 3: Composition/information on ingredients**

### 3.2 Mixtures

# **Hazardous components**

Chemical name	CAS-No.	Classification	Concentration
	EC-No.	(SANS 10234)	(% w/w)
	Registration number		
Hexamethylene-1,6-diisocyanate	28182-81-2	Acute Tox.4; H332	>=80
homopolymer		Skin Sens.1; H317	
Contains:	01-2119485796-17-	STOT SE3; H335	
hexamethylene-di-isocyanate <= 0,3	XXXX		
%			

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



# Sikafloor 304/305 W Part B

Poly(oxy-1,2-ethanediyl), .alpha tridecylomegahydroxy-, phosphate	9046-01-9	Skin Irrit.2; H315 Eye Dam.1; H318 Aquatic Chronic2; H411	>= 3 - < 5
cyclohexyldimethylamine	98-94-2 202-715-5 01-2119533030-60- XXXX	Flam. Liq.3; H226 Acute Tox.3; H301 Acute Tox.3; H331 Acute Tox.3; H311 Skin Corr.1B; H314 Eye Dam.1; H318 Aquatic Chronic2; H411	>= 0,25 - < 1

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

## 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Cough

Respiratory disorder Allergic reactions Excessive lachrymation

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



# Sikafloor 304/305 W Part B

Revision Date 24.03.2021 Version 1.1 Print Date 24.03.2021

Headache

See Section 11 for more detailed information on health effects

and symptoms.

Risks : irritant effects

sensitising effects

May cause an allergic skin reaction.

Causes serious eye damage.

Harmful if inhaled.

May cause respiratory irritation.

### 4.3 Indication of any immediate medical attention and special treatment needed

: Treat symptomatically. **Treatment** 

### **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

#### 5.2 Special hazards arising from the substance or mixture

ucts

Hazardous combustion prod- : No hazardous combustion products are known

# 5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Deny access to unprotected persons.

#### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



# Sikafloor 304/305 W Part B

Revision Date 24.03.2021 Version 1.1 Print Date 24.03.2021

# 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For personal protection see section 8.

### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Provide sufficient air exchange and/or exhaust in work rooms. Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



# Sikafloor 304/305 W Part B

Revision Date 24.03.2021 Version 1.1 Print Date 24.03.2021

### 7.3 Specific end use(s)

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Hexamethylene- 1,6-diisocyanate homopolymer	28182-81-2	TWA OEL-CL	0,02 mg/m3 (Cyanide)	ZA OEL
	Further information: Control Limit, Sensitisers that may cause sensitisation by inhalation			
		STEL OEL-CL	0,07 mg/m3 (Cyanide)	ZA OEL

#### 8.2 Exposure controls

#### Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in par-

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



# Sikafloor 304/305 W Part B

Revision Date 24.03.2021 Version 1.1 Print Date 24.03.2021

ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used. Ensure adequate ventilation, especially in confined areas.

# **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

Appearance : liquid
Colour : colourless
Odour : odourless

Odour Threshold : No data available

pH : Not applicable substance/mixture reacts with water

No data available

Melting point/range / Freezing :

point

Boiling point/boiling range : > 150 °C

Flash point : 100 °C

Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

: No data available

Vapour pressure : 0,01 hPa

Relative vapour density : No data available

Density : ca. 1,13 g/cm3 (20 °C)

Solubility(ies)

Water solubility : partly soluble Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



# Sikafloor 304/305 W Part B

Revision Date 24.03.2021 Version 1.1 Print Date 24.03.2021

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20,5 mm2/s (40 °C)

Explosive properties : No data available

Oxidizing properties : No data available

#### 9.2 Other information

No data available

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

# 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

## 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

# **SECTION 11: Toxicological information**

# 11.1 Information on toxicological effects

### **Acute toxicity**

Harmful if inhaled.

### **Components:**

### Hexamethylene-1,6-diisocyanate homopolymer:

Acute oral toxicity : LD50 Oral (Rat): > 2.500 mg/kg

Acute inhalation toxicity : LC50: 1,5 mg/l

Exposure time: 4 h

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



# Sikafloor 304/305 W Part B

Revision Date 24.03.2021 Version 1.1 Print Date 24.03.2021

Test atmosphere: dust/mist Method: Expert judgement

Acute dermal toxicity : LD50 Dermal (Rat): > 2.000 mg/kg

cyclohexyldimethylamine:

Acute inhalation toxicity : LC50 (Rat): 4,45 mg/l

Exposure time: 4 h
Test atmosphere: vapour

#### Skin corrosion/irritation

Not classified based on available information.

### Serious eye damage/eye irritation

Causes serious eye damage.

#### Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

# Reproductive toxicity

Not classified based on available information.

# STOT - single exposure

May cause respiratory irritation.

### STOT - repeated exposure

Not classified based on available information.

### **Aspiration toxicity**

Not classified based on available information.

# **SECTION 12: Ecological information**

### 12.1 Toxicity

No data available

#### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



# Sikafloor 304/305 W Part B

### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

#### **Product:**

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

#### 12.6 Other adverse effects

#### **Product:**

Additional ecological infor-

mation

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

# **SECTION 13: Disposal considerations**

## 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

European Waste Catalogue : 08 04 09\* waste adhesives and sealants containing organic

solvents or other dangerous substances

Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated

by dangerous substances

## **SECTION 14: Transport information**

# 14.1 UN number

Not regulated as a dangerous good

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



# Sikafloor 304/305 W Part B

Revision Date 24.03.2021 Version 1.1 Print Date 24.03.2021

# 14.2 UN proper shipping name

Not regulated as a dangerous good

### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

#### 14.4 Packing group

Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good

### 14.6 Special precautions for user

Not applicable

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

## **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)

Number on list 3 : Not applicable

(=> 0.1 %).

Not applicable

Conditions of restriction for the fol-

None of the components are listed

lowing entries should be considered:

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

REACH - List of substances subject to authorisation

(Annex XIV)

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals **REACH Information:** 

Not applicable Not applicable

Not applicable

All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

- excluded from the regulation, and/or - exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



# Sikafloor 304/305 W Part B

Revision Date 24.03.2021 Version 1.1 Print Date 24.03.2021

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV) no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 0,9 %

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

H226 : Flammable liquid and vapour.

H301 : Toxic if swallowed.

H311 : Toxic in contact with skin.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction. H318 : Causes serious eye damage.

H331 : Toxic if inhaled. H332 : Harmful if inhaled.

H335 : May cause respiratory irritation.

H411 : Toxic to aquatic life with long lasting effects.

#### Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage
Flam. Liq. : Flammable liquids
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

STOT SE : Specific target organ toxicity - single exposure

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road Chemical Abstracts Service

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



# Sikafloor 304/305 W Part B

Revision Date 24.03.2021 Version 1.1 Print Date 24.03.2021

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

## Classification of the mixture: Classification procedure:

Acute Tox. 4	H332	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
STOT SE 3	H335	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

ZA / EN