

#### HASSLE-FREE WATERPROOFING

Waterproofing just got better and easier with Sealoflex Professional, an acrylic based fibre reinforced waterproofer. Just two coats of this membrane-free waterproofing solution will make roof leaks a thing of the past.



# What you will need to waterproof your roof

- High-pressure cleaner or bucket and brush
- Wire brush
- Sika Sealoflex Professional

\_\_\_\_\_

Paint brush

## Step 1

Check the weather and make sure it's not going to rain. Use soap and a brush to scrub off any superficial rust. Then clean the flashing or area of your roof you want to waterproof with a high pressure cleaner and allow it to dry. Steel surfaces need to be coated with a good metal primer.

### Step 2

Stir the Sealoflex Professional, a high-quality acrylic fibre-reinforced waterproofer, with a flat paddle until the mixture is smooth. Brush it on, forming an even layer of 1 mm thick (11/m2) over the flashing and onto the roof. Clean your brush immediately with water. Allow the Sealoflex to dry for approximately four hours or until it is dry to the touch.



### Step 3

Apply a second coat, again to a thickness of 1 mm, and allow to dry. Clean your brush with water.



#### **IDEAL FOR USE ON**

- Flat roofs
- Tiled roofs
- Flashing
- Iron and steel surfaces
- Over-coating existing waterproofing membrane



#### SIKA'S TIP:

If one of the four standard Sealoflex Professional colours doesn't match your roof, you can paint over it in the colour of your choice.

