According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



# **Everbuild Gator Glue**

Revision Date 01.02.2021 Version 1.0 Print Date 01.02.2021

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Everbuild Gator Glue

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika South Africa (Pty) Ltd

9 Hocking Place Westmead 3608 Pinetown South Africa

Telephone : +27 (0)31 792 6500
Telefax : +27 (0)31 700 1760
E-mail address of person : headoffice@za.sika.com

responsible for the SDS

1.4 Emergency telephone number

+27 82 490 9409

#### **SECTION 2: Hazards identification**

Type of product : Mixture

#### 2.1 Classification of the substance or mixture

Specific target organ toxicity - repeated

### Classification (SANS 10234)

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Respiratory sensitisation, Category 1 H334: May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

H373: May cause damage to organs through pro-

Skin sensitisation, Category 1

Carcinogenicity, Category 2

H317: May cause an allergic skin reaction.
H351: Suspected of causing cancer.
H335: May cause respiratory irritation

Specific target organ toxicity - single exposure, Category 3, Respiratory system

exposure, Category 2 longed or repeated exposure.

### 2.2 Label elements

### Labelling (SANS 10234)

Hazard pictograms :





According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



# **Everbuild Gator Glue**

Revision Date 01.02.2021	ersion 1.0	Print Date 01.02.2021
--------------------------	------------	-----------------------

Signal word Danger Causes skin irritation. Hazard statements H315 May cause an allergic skin reaction. H317 Causes serious eve irritation. H319 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. H335 Suspected of causing cancer. H351 H373 May cause damage to organs through prolonged or repeated exposure. If medical advice is needed, have product Precautionary statements : P101 container or label at hand. Keep out of reach of children. P102 Prevention: P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P284 In case of inadequate ventilation wear respiratory protection. Response: P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. IF exposed or concerned: Get medical ad-P308 + P313 vice/ attention. Storage: P405 Store locked up. Disposal: P501 Dispose of contents/container in accordance with local regulation.

Hazardous components which must be listed on the label: methylenediphenyl diisocyanate

### Additional Labelling:

EUH204 Contains isocyanates. May produce an allergic reaction.

Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



# **Everbuild Gator Glue**

Revision Date 01.02.2021 Version 1.0 Print Date 01.02.2021

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

### **Hazardous components**

Chemical name	CAS-No. EC-No.	Classification (SANS 10234)	Concentration (% w/w)
	Registration number		
methylenediphenyl diisocyanate	26447-40-5	Acute Tox.4; H332	>= 25 - < 40
	1	Skin Irrit.2; H315	
	01-2119457015-45-	Eye Irrit.2; H319	
	XXXX	Resp. Sens.1;	
		H334	
		Skin Sens.1; H317	
		Carc.2; H351	
		STOT SE3; H335	
		STOT RE2; H373	

For explanation of abbreviations see section 16.

### **SECTION 4: First aid measures**

# 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



# **Everbuild Gator Glue**

Print Date 01.02.2021 Revision Date 01.02.2021 Version 1.0

#### 4.2 Most important symptoms and effects, both acute and delayed

**Symptoms** : Asthmatic appearance

Cough

Respiratory disorder Allergic reactions **Excessive lachrymation** 

Erythema **Dermatitis** 

See Section 11 for more detailed information on health effects

and symptoms.

Risks : irritant effects

> sensitising effects Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

May cause respiratory irritation. Suspected of causing cancer.

May cause damage to organs through prolonged or repeated

exposure.

### 4.3 Indication of any immediate medical attention and special treatment needed

**Treatment** : Treat symptomatically.

### **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

# 5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod-

ucts

: No hazardous combustion products are known

### 5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



# **Everbuild Gator Glue**

Revision Date 01.02.2021 Version 1.0 Print Date 01.02.2021

#### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store in original container. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



# **Everbuild Gator Glue**

Revision Date 01.02.2021 Version 1.0 Print Date 01.02.2021

must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Store in accordance with

local regulations.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

### **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

#### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
methylenediphenyl diisocyanate	26447-40-5	TWA OEL-RL	0,02 mg/m3	ZA OEL
	Further information: Sensitisers that may cause sensitisation by inhalation, Recommended Limit			
		STEL OEL-RL	0,07 mg/m3	ZA OEL

### 8.2 Exposure controls

### Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : Respirator selection must be based on known or anticipated

exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as-

sessment indicates this is necessary.

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



# **Everbuild Gator Glue**

Revision Date 01.02.2021 Version 1.0 Print Date 01.02.2021

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

### **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

Appearance : liquid
Colour : various
Odour : musty

Odour Threshold : No data available

pH : Not applicable

Melting point/range / Freezing :

point

No data available

Boiling point/boiling range : No data available

Flash point : > 200 °C

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : 0,01 hPa

Relative vapour density : No data available

Density : ca. 1,12 g/cm3 (20 °C)

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : No data available

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



# **Everbuild Gator Glue**

Revision Date 01.02.2021 Version 1.0 Print Date 01.02.2021

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 7 mm2/s (40 °C)

Explosive properties : No data available

Oxidizing properties : No data available

#### 9.2 Other information

No data available

# **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

#### 10.4 Conditions to avoid

Conditions to avoid : Avoid moisture.

# 10.5 Incompatible materials

Materials to avoid : No data available

# 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

# **SECTION 11: Toxicological information**

# 11.1 Information on toxicological effects

### **Acute toxicity**

No data available

#### Skin corrosion/irritation

Causes skin irritation.

### Serious eye damage/eye irritation

Causes serious eye irritation.

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



# **Everbuild Gator Glue**

Revision Date 01.02.2021 Version 1.0 Print Date 01.02.2021

### Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

#### Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

Suspected of causing cancer.

### Reproductive toxicity

Not classified based on available information.

### STOT - single exposure

May cause respiratory irritation.

#### STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

### **Aspiration toxicity**

Not classified based on available information.

### **SECTION 12: Ecological information**

### 12.1 Toxicity

No data available

#### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

### **Product:**

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

#### 12.6 Other adverse effects

### **Product:**

Additional ecological infor-

mation

: There is no data available for this product.

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



# **Everbuild Gator Glue**

Revision Date 01.02.2021 Version 1.0 Print Date 01.02.2021

### **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated

by dangerous substances

### **SECTION 14: Transport information**

#### 14.1 UN number

Not regulated as a dangerous good

### 14.2 UN proper shipping name

Not regulated as a dangerous good

### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

#### 14.4 Packing group

Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good

### 14.6 Special precautions for user

Not applicable

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

### **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on : Conditions of restriction for the fol-

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



# **Everbuild Gator Glue**

Revision Date 01.02.2021 Version 1.0 Print Date 01.02.2021

the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

lowing entries should be considered: methylenediphenyl diisocyanate

None of the components are listed

(Number on list 56)

Not applicable

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

(=> 0.1 %).REACH - List of substances subject to authorisation Not applicable

(Annex XIV)

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Regulation (EC) No 850/2004 on persistent organic pol-Not applicable

lutants

**REACH Information:** All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

- excluded from the regulation, and/or - exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Volatile organic compounds Law on the incentive tax for volatile organic compounds

> (VOCV) no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)

Not applicable

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

### **SECTION 16: Other information**

### **Full text of H-Statements**

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. Causes serious eye irritation. H319

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

May cause respiratory irritation. H335 Suspected of causing cancer. H351

H373 May cause damage to organs through prolonged or repeated

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



# **Everbuild Gator Glue**

Revision Date 01.02.2021 Version 1.0 Print Date 01.02.2021

exposure.

#### Full text of other abbreviations

Acute Tox. Acute toxicity Carcinogenicity Carc. Eve Irrit. Eve irritation

Resp. Sens. Respiratory sensitisation

Skin Irrit. Skin irritation Skin Sens. Skin sensitisation

STOT RE Specific target organ toxicity - repeated exposure Specific target organ toxicity - single exposure STOT SE

European Agreement concerning the International Carriage of **ADR** 

Dangerous Goods by Road

Chemical Abstracts Service CAS Derived no-effect level **DNEL** 

EC50 Half maximal effective concentration

Globally Harmonized System **GHS** International Air Transport Association IATA

International Maritime Code for Dangerous Goods **IMDG** 

LD50

Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

**MARPOL** International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL Occupational Exposure Limit

PBT Persistent, bioaccumulative and toxic **PNEC** Predicted no effect concentration

Regulation (EC) No 1907/2006 of the European Parliament REACH

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

**SVHC** Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

#### Classification of the mixture: Classification procedure:

Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Resp. Sens. 1	H334	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 2	H351	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



# **Everbuild Gator Glue**

Revision Date 01.02.2021 Version 1.0

Print Date 01.02.2021

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

ZA / EN