According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Sikafloor 21 Purcem C

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikafloor 21 Purcem C

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Flooring system

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika South Africa (Pty) Ltd

9 Hocking Place Westmead 3608 Pinetown South Africa

Telephone : +27 (0)31 792 6500
Telefax : +27 (0)31 700 1760
E-mail address of person : headoffice@za.sika.com

responsible for the SDS

1.4 Emergency telephone number

+27 76 920 1930

SECTION 2: Hazards identification

Type of product : Mixture

2.1 Classification of the substance or mixture

Classification (SANS 10234)

Skin irritation, Category 2 H315: Causes skin irritation.

Serious eye damage, Category 1 H318: Causes serious eye damage. Specific target organ toxicity - single exposure, Category 3, Respiratory system

2.2 Label elements

Labelling (SANS 10234)

Hazard pictograms





Signal word : Danger

Hazard statements : H315 Causes skin irritation.

H318 Causes serious eye damage. H335 May cause respiratory irritation.

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Sikafloor 21 Purcem C

Revision Date 07.06.2022 Version 2.0 Print Date 07.06.2022

Precautionary statements : P101 If medical advice is needed, have product

container or label at hand.

P102 Keep out of reach of children.

Prevention:

P271 Use only outdoors or in a well-ventilated

area.

P280 Wear protective gloves/ eye protection/ face

protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a

POISON CENTER/ doctor.

Disposal:

P501 Dispose of contents/container in accord-

ance with local regulation.

Hazardous components which must be listed on the label:

Cement (chromium reduced)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

The content of soluble Chromium (VI) is not greater than 0,0002% in accordance with Annex XVII, Paragraph 47 of the EU Regulation 1907/2006.

The product reacts highly alkaline with water.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No.	Classification	Concentration		
	EC-No.	(SANS 10234)	(% w/w)		
	Registration number				
Cement (chromium reduced)	65997-15-1	Skin Irrit.2; H315	>= 25 - < 40		
	266-043-4	Eye Dam.1; H318 STOT SE3; H335			
calcium dihydroxide	1305-62-0	Skin Irrit.2; H315	>= 1 - < 2,5		
	215-137-3	Eye Dam.1; H318			
	01-2119475151-45-	STOT SE3; H335			
	XXXX				
Substances with a workplace exposure limit :					
Quartz (SiO2)	14808-60-7		>= 60 - < 80		
	238-878-4				

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Sikafloor 21 Purcem C

Quartz (SiO2)	14808-60-7		>= 5 - < 10
	238-878-4	!	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Cough

Respiratory disorder Excessive lachrymation

Erythema Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Risks : irritant effects

Causes skin irritation.

Causes serious eye damage. May cause respiratory irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Sikafloor 21 Purcem C

Revision Date 07.06.2022 Version 2.0 Print Date 07.06.2022

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

5.2 Special hazards arising from the substance or mixture

ucts

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Avoid breathing dust.

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Try to prevent the material from entering drains or water

courses.

No special environmental precautions required.

6.3 Methods and material for containment and cleaning up

: Pick up and arrange disposal without creating dust. Methods for cleaning up

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Avoid exceeding the given occupational exposure limits (see

section 8).

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Sikafloor 21 Purcem C

Version 2.0 Print Date 07.06.2022 Revision Date 07.06.2022

> Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Advice on protection against :

fire and explosion

Avoid dust formation. Provide appropriate exhaust ventilation

at places where dust is formed.

Hygiene measures Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated

place. Store in accordance with local regulations.

Further information on stor-

age stability

Keep in a dry place.

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis	
Quartz (SiO2)	14808-60-7	OEL- ML (respirable dust fraction)	0,1 mg/m3	ZA OEL	
	Further information: Occupational Exposure Limits - Maximum Limits For Hazardous Chemical Agents, denotes carcinogenicity, which is based on GHS categorisation, including category 1A, 1B				
Quartz (SiO2)	14808-60-7	OEL- ML (respirable dust fraction)	0,1 mg/m3	ZA OEL	
	Further information: Occupational Exposure Limits - Maximum Limits For Hazardous Chemical Agents, denotes carcinogenicity, which is based on GHS categorisation, including category 1A, 1B				
calcium dihydrox- ide	1305-62-0	TWA (Respirable fraction)	1 mg/m3	2017/164/EU	
	Further information: Indicative				
		STEL (Respira- ble fraction)	4 mg/m3	2017/164/EU	
		OEL-RL	10 mg/m3	ZA OEL	
	Further information: Occupational Exposure Limits - Restricted Limits For Hazardous Chemical Agents				

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Sikafloor 21 Purcem C

Revision Date 07.06.2022 Version 2.0 Print Date 07.06.2022

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Recommended: Butyl rubber/nitrile rubber gloves.

Contaminated gloves should be removed.

Skin and body protection : Dust impervious protective suit

Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

particulate filter P

P1: Inert material; P2, P3: hazardous substances

Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : solid
Appearance : powder
Colour : white
Odour : odourless

Melting point/range / Freezing :

point

No data available

Boiling point/boiling range : No data available

Flammability (solid, gas) : No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Up- : No data available

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Sikafloor 21 Purcem C

per flammability limit

Lower explosion limit / Lower flammability limit

: No data available

Flash point : Not applicable

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : > 11 (20 °C)

Concentration: 50 %

Viscosity

Viscosity, kinematic : Not applicable

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

No data available

Vapour pressure : No data available

Density : No data available

Bulk density : ca. 1.480 kg/m3 (20 °C)

Relative vapour density : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Sikafloor 21 Purcem C

Revision Date 07.06.2022 Version 2.0 Print Date 07.06.2022

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

No data available

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Sikafloor 21 Purcem C

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting poten-

tial

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to

REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Additional ecological infor-

mation

: There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

European Waste Catalogue : 16 03 03* inorganic wastes containing dangerous substances

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated

by dangerous substances

SECTION 14: Transport information

14.1 UN number

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Sikafloor 21 Purcem C

Revision Date 07.06.2022 Version 2.0 Print Date 07.06.2022

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:

Cement (chromium reduced) (Number on list 47)

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors

: Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).

None of the components are listed

(=> 0.1 %).

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Sikafloor 21 Purcem C

Revision Date 07.06.2022 Version 2.0 Print Date 07.06.2022

REACH - List of substances subject to authorisation : Not applicable

(Annex XIV)

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Regulation (EC) No 649/2012 of the European Parlia-

ment and the Council concerning the export and import

of dangerous chemicals

REACH Information: All substances contained in our Products are

- registered by our upstream suppliers, and/or

Not applicable

Not applicable

Not applicable

- registered by us, and/or

excluded from the regulation, and/orexempted from the registration.

- exempled from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV)

no VOC duties

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H315 : Causes skin irritation.

H318 : Causes serious eye damage. H335 : May cause respiratory irritation.

Full text of other abbreviations

Eye Dam. : Serious eye damage

Skin Irrit. : Skin irritation

STOT SE : Specific target organ toxicity - single exposure

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration
GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Sikafloor 21 Purcem C

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Classification of the mixture: Classification procedure:

Skin Irrit. 2 H315 Calculation method
Eye Dam. 1 H318 Calculation method
STOT SE 3 H335 Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

ZA / EN