

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikalastic-625

Revision Date 14.02.2023

Version 1.0

Print Date 14.02.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Sikalastic-625

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Polyurethane coating

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika South Africa (Pty) Ltd  
9 Hocking Place  
Westmead  
3608 Pinetown  
South Africa  
Telephone : +27 (0)31 792 6500  
Telefax : +27 (0)31 700 1760  
E-mail address of person responsible for the SDS : headoffice@za.sika.com

#### 1.4 Emergency telephone number

+27 76 920 1930

### SECTION 2: Hazards identification

Type of product : Mixture

#### 2.1 Classification of the substance or mixture

##### Classification (SANS 10234)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (SANS 10234)

Hazard pictograms :



Signal word : Warning

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikalastic-625

Revision Date 14.02.2023

Version 1.0

Print Date 14.02.2023

Hazard statements	: H226 H315 H317 H319 H336 H411	Flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.
Precautionary statements	: <b>Prevention:</b> P210  P261 P273 P280  <b>Response:</b> P370 + P378  P391	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing mist or vapours. Avoid release to the environment. Wear protective gloves/ protective clothing/ eye protection/ face protection.  In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. Collect spillage.

Hazardous components which must be listed on the label:

2-methoxy-1-methylethyl acetate  
Pentamethyl piperidylsebacate  
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate  
4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT)

### Additional Labelling:

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

"As from 24 August 2023 adequate training is required before industrial or professional use."

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (SANS 10234)	Concentration (% w/w)
2-methoxy-1-methylethyl acetate Contains:	108-65-6 203-603-9	Flam. Liq.3; H226 STOT SE3; H336	>= 20 - < 25

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikalastic-625

Revision Date 14.02.2023

Version 1.0

Print Date 14.02.2023

2-methoxypropyl acetate <= 1 %	01-2119475791-29-XXXX		
Titanium dioxide (> 10 µm)	13463-67-7 236-675-5 01-2119489379-17-XXXX		>= 5 - < 10
Pentamethyl piperidylsebacate Contains: bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	1065336-91-5 01-2119491304-40-XXXX	Skin Sens.1A; H317 Repr.2; H361f Aquatic Acute1; H400 Aquatic Chronic1; H410	>= 0,25 - < 1
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9 223-861-6 01-2119490408-31-XXXX	Acute Tox.1; H330 Skin Irrit.2; H315 Eye Irrit.2; H319 Resp. Sens.1; H334 Skin Sens.1; H317 STOT SE3; H335 Aquatic Chronic2; H411	>= 0,25 - < 0,5
2-ethylhexanoic acid, zirconium salt	22464-99-9 245-018-1 01-2119979088-21-XXXX	Repr.2; H361d	< 1
4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT)	64359-81-5 264-843-8	Acute Tox.4; H302 Acute Tox.2; H330 Skin Corr.1; H314 Eye Dam.1; H318 Skin Sens.1A; H317 Aquatic Acute1; H400 Aquatic Chronic1; H410	>= 0,1 - < 0,25

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikalastic-625

Revision Date 14.02.2023

Version 1.0

Print Date 14.02.2023

---

- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Allergic reactions  
Excessive lachrymation  
Erythema  
Dermatitis  
Loss of balance  
Vertigo  
See Section 11 for more detailed information on health effects and symptoms.
- Risks : irritant effects  
sensitising effects  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.
- 

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : Water  
High volume water jet

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikalastic-625

Revision Date 14.02.2023

Version 1.0

Print Date 14.02.2023

---

### 5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.  
Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Further information : Use water spray to cool unopened containers.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- 

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Use personal protective equipment.  
Remove all sources of ignition.  
Deny access to unprotected persons.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

- Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

- For personal protection see section 8.
- 

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Country ZA 100000014454

5 / 17

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikalastic-625

Revision Date 14.02.2023

Version 1.0

Print Date 14.02.2023

- Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharge.  
Open drum carefully as content may be under pressure.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
Follow standard hygiene measures when handling chemical products
- Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.
- Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

- Specific use(s) : Consult most current local Product Data Sheet prior to any use.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-methoxy-1-methylethyl acetate	108-65-6	STEL	100 ppm 550 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikalastic-625

Revision Date 14.02.2023

Version 1.0

Print Date 14.02.2023

		TWA	50 ppm 275 mg/m <sup>3</sup>	2000/39/EC
Titanium dioxide (> 10 µm)	13463-67-7	OEL-RL	10 mg/m <sup>3</sup>	ZA OEL
	Further information: Occupational Exposure Limits - Restricted Limits For Hazardous Chemical Agents, denotes carcinogenicity, which is based on GHS categorisation, including category 1A, 1B			
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9	OEL-RL	0,01 ppm	ZA OEL
	Further information: Occupational Exposure Limits - Restricted Limits For Hazardous Chemical Agents			

### 8.2 Exposure controls

#### Engineering measures

Maintain air concentrations below occupational exposure standards.  
Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166  
Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm)

Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm),  
breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
organic vapor (Type A) and particulate filter  
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm  
P1: Inert material; P2, P3: hazardous substances  
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in par-

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikalastic-625

Revision Date 14.02.2023

Version 1.0

Print Date 14.02.2023

ticular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state : liquid  
Colour : various  
Odour : hydrocarbon-like

Melting point/range / Freezing point : No data available

Boiling point/boiling range : No data available

Flammability (solid, gas) : No data available

#### Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : 10,8 %(V)

Lower explosion limit / Lower flammability limit : 1,5 %(V)

Flash point : ca. 52 °C  
Method: closed cup

Auto-ignition temperature : 333 °C

Decomposition temperature : No data available

pH : Not applicable

#### Viscosity

Viscosity, dynamic : ca. 1.800 mPa.s (20 °C)

Viscosity, kinematic : > 20,5 mm<sup>2</sup>/s (40 °C)

#### Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 3,1 hPa

Density : ca. 1,31 g/cm<sup>3</sup> (20 °C)



# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikalastic-625

Revision Date 14.02.2023

Version 1.0

Print Date 14.02.2023

---

Relative vapour density : No data available

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : No data available

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Not classified based on available information.

#### Components:

##### **2-methoxy-1-methylethyl acetate:**

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

##### **Pentamethyl piperidylsebacate:**

Acute oral toxicity : LD50 Oral (Rat): 3.230 mg/kg

##### **3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate:**

Acute oral toxicity : LD50 Oral (Rat): 4.814 mg/kg

---

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikalastic-625

Revision Date 14.02.2023

Version 1.0

Print Date 14.02.2023

Acute inhalation toxicity : LC50 (Rat): 0,031 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute toxicity estimate: 0,031 mg/l  
Test atmosphere: dust/mist  
Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rat): > 7.000 mg/kg

### **4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT):**

Acute oral toxicity : Acute toxicity estimate: 567 mg/kg  
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

Acute inhalation toxicity : Acute toxicity estimate: 0,16 mg/l  
Test atmosphere: dust/mist  
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

### **Skin corrosion/irritation**

Causes skin irritation.

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

### **Respiratory or skin sensitisation**

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

### **Germ cell mutagenicity**

Not classified based on available information.

### **Carcinogenicity**

Not classified based on available information.

### **Reproductive toxicity**

Not classified based on available information.

### **STOT - single exposure**

May cause drowsiness or dizziness.

### **STOT - repeated exposure**

Not classified based on available information.

### **Aspiration toxicity**

Not classified based on available information.

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikalastic-625

Revision Date 14.02.2023

Version 1.0

Print Date 14.02.2023

---

### SECTION 12: Ecological information

#### 12.1 Toxicity

**Components:**

**Pentamethyl piperidylsebacate:**

Toxicity to fish : LC50 (Fish): 0,97 mg/l  
Exposure time: 96 h

M-Factor (Short-term (acute) aquatic hazard) : 1

M-Factor (Long-term (chronic) aquatic hazard) : 1

**4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT):**

Toxicity to fish : LC50 (Fish): 0,0027 mg/l  
Exposure time: 96 h

M-Factor (Short-term (acute) aquatic hazard) : 100

M-Factor (Long-term (chronic) aquatic hazard) : 100

#### 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### 12.6 Other adverse effects

**Product:**

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Additional ecological information : An environmental hazard cannot be excluded in the event of

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikalastic-625

Revision Date 14.02.2023

Version 1.0

Print Date 14.02.2023

mation unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.  
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.  
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated by dangerous substances

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADR : UN 1263  
IMDG : UN 1263  
IATA : UN 1263

#### 14.2 UN proper shipping name

ADR : PAINT RELATED MATERIAL  
IMDG : PAINT RELATED MATERIAL  
IATA : Paint related material

#### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	: 3	
IMDG	: 3	
IATA	: 3	

#### 14.4 Packing group

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikalastic-625

Revision Date 14.02.2023

Version 1.0

Print Date 14.02.2023

### ADR

Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : (D/E)  
Remarks : Exempted according to 2.2.3.1.5 (Viscous substance exemption)

### IMDG

Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Remarks : Transport in accordance with 2.3.2.5 of the IMDG-Code

### IATA (Cargo)

Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

### IATA (Passenger)

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

## 14.5 Environmental hazards

### ADR

Environmentally hazardous : no

### IMDG

Marine pollutant : no

### IATA (Passenger)

Environmentally hazardous : no

### IATA (Cargo)

Environmentally hazardous : no

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikalastic-625

Revision Date 14.02.2023

Version 1.0

Print Date 14.02.2023

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 3

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate  
(Number on list 74)

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed  
(=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH Information: All substances contained in our Products are  
- registered by our upstream suppliers, and/or  
- registered by us, and/or  
- excluded from the regulation, and/or  
- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

E2 ENVIRONMENTAL HAZARDS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)  
Volatile organic compounds (VOC) content: 24,21% w/w

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikalastic-625

Revision Date 14.02.2023

Version 1.0

Print Date 14.02.2023

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 24,21% w/w

### Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

## SECTION 16: Other information

### Full text of H-Statements

H226	: Flammable liquid and vapour.
H302	: Harmful if swallowed.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H330	: Fatal if inhaled.
H334	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H361d	: Suspected of damaging the unborn child.
H361f	: Suspected of damaging fertility.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Repr.	: Reproductive toxicity
Resp. Sens.	: Respiratory sensitisation
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
ZA OEL	: South Africa. The Regulations for Hazardous Chemical Agents, Occupational Exposure Limits

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikalastic-625

Revision Date 14.02.2023

Version 1.0

Print Date 14.02.2023

2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
ZA OEL / OEL-RL	: Occupational Exposure Limit Restricted limit - 8- hour exposure or equivalent (12 hour shifts)
ADR	: European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	: Chemical Abstracts Service
DNEL	: Derived no-effect level
EC50	: Half maximal effective concentration
GHS	: Globally Harmonized System
IATA	: International Air Transport Association
IMDG	: International Maritime Code for Dangerous Goods
LD50	: Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	: Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	: International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	: Occupational Exposure Limit
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
vPvB	: Very persistent and very bioaccumulative

### Further information

#### Classification of the mixture:

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
STOT SE 3	H336
Aquatic Chronic 2	H411

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !



# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and  
Hazardous Chemical Substance Regs. (GNR. 1179 of 25 Au-  
gust 1995)



## Sikalastic-625

Revision Date 14.02.2023

Version 1.0

Print Date 14.02.2023

---

ZA / EN