

1.1 Product identifier Trade name

Revision Date 15.02.2020	Version 2.0	Print Date 15.02.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

: Sikadur 330 Comp. A

Product use	the substance or mixture and uses advised against : Adhesive
1.3 Details of the supplier of the	e safety data sheet
Company name of supplier	: Sika South Africa (Pty) Ltd 9 Hocking Place Westmead 3608 Pinetown South Africa
Telephone Telefax E-mail address of person responsible for the SDS	: +27 (0)31 792 6500 : +27 (0)31 700 1760 : headoffice@za.sika.com

1.4 Emergency telephone number

+27 82 490 9409

SECTION 2: Hazards identification

Type of product : Mixture

2.1 Classification of the substance or mixture

Classification (SANS 10234)


Skin irritation, Category 2 Serious eye damage, Category 1 Skin sensitisation, Category 1 Long-term (chronic) aquatic hazard, Category 2


- H317: May ca
- H317: May cause an allergic skin reaction.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H411: Toxic to aquatic life with long lasting effects.







Revision Date 15.02.2020	Version	2.0	Print Date 15.02.2020
I	H411	Toxic to aquatic life	e with long lasting effects.
Precautionary statements :	Prevention:		
,	P261	Avoid breathing du pours/ spray.	ıst/ fume/ gas/ mist/ va-
	P264	Wash skin thoroug	hly after handling.
	P273	Avoid release to th	
	P280	Wear protective gloprotection.	oves/ eye protection/ face
	Response:	•	
	P305 + P351 + F	with water for seve	
	P391	Collect spillage.	

Hazardous components which must be listed on the label:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) 1,4-bis(2,3 epoxypropoxy)butane

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.	(SANS 10234)	(% w/w)
	Registration number		. ,
reaction product: bisphenol-A-	25068-38-6	Eye Irrit.2; H319	>= 40 - < 60
(epichlorhydrin); epoxy resin (number		Skin Irrit.2; H315	
average molecular weight ≤ 700)	01-2119456619-26-	Skin Sens.1; H317	
	XXXX	Aquatic Chronic2;	
		H411	
1,4-bis(2,3 epoxypropoxy)butane	2425-79-8	Aquatic Chronic3;	>= 10 - < 20
	219-371-7	H412	
	01-2119494060-45-	Acute Tox.4; H302	
	XXXX	Acute Tox.4; H332	
		Acute Tox.4; H312	
		Skin Irrit.2; H315	
		Skin Sens.1; H317	
		Eye Dam.1; H318	
Hydrocarbons, C10-C13, aromatics,	64742-94-5	Asp. Tox.1; H304	>= 2,5 - < 5
<1% naphthalene		Aquatic Chronic2;	



Revision Date 15.02.2020	Version 2.0	Print Date 15.02.2020
Contains: naphthalene <= 1 %	01-2119451097-39- XXXX	H411

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures General advice : Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance. If inhaled : Move to fresh air. Consult a physician after significant exposure. In case of skin contact : Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician. : Small amounts splashed into eyes can cause irreversible tis-In case of eye contact sue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing. If swallowed : Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. 4.2 Most important symptoms and effects, both acute and delayed Symptoms : Allergic reactions Excessive lachrymation Erythema Dermatitis See Section 11 for more detailed information on health effects and symptoms. : irritant effects Risks sensitising effects Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage.



Revision Date 15.02.2020	Version 2.0	Print Date 15.02.2020

4.3 Indication of any immediate medical attention and special treatment needed

Treatment

: Treat symptomatically.

SECTION 5: Firefighting measures

5.1	Extinguishing media	
0.1	Exanguisting mould	

for firefighters

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire- fighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion prod- ucts	:	No hazardous combustion products are known
5.3 Advice for firefighters Special protective equipment	:	In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. The must not be discharged into drains. Fire residues and contaminated fire extinguishing water mube disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures				
Personal precautions	:	Use personal protective equipment. Deny access to unprotected persons.		

6.2 Environmental precautions

Environmental precautions	 Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.
	•

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel,
	acid binder, universal binder, sawdust).
	Keep in suitable, closed containers for disposal.



Revision Date 15.02.2020	Version 2.0	Print Date 15.02.2020
Nevision Date 15.02.2020	Version 2.0	1 mill Date 15.02.2020

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	 Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products
Advice on protection against fire and explosion	: Normal measures for preventive fire protection.
Hygiene measures	: Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2 Conditions for safe storage, i	ncluding any incompatibilities
Requirements for storage areas and containers	: Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.
Other data	: No decomposition if stored and applied as directed.
7.3 Specific end use(s)	
Specific use(s)	: Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Personal protective equipment

Eye protection	: Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	: Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling



Revision Date 15.02.2020	Version 2.0	Print Date 15.02.2020
	chemical products. Reference n facturer specifications.	umber EN 374. Follow manu-
	Suitable for short time use or pr Butyl rubber/nitrile rubber gloves Contaminated gloves should be Suitable for permanent exposur Viton gloves (0.4 mm), breakthrough time >30 min.	s (0,4 mm) removed.
Skin and body protection	: Protective clothing (e.g. Safety s long-sleeved working clothing, lo and protective boots are additio and stirring work.	ong trousers). Rubber aprons
Respiratory protection	 Respirator selection must be ba exposure levels, the hazards of ing limits of the selected respira organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 pp Ensure adequate ventilation. Th exhaust extraction or by genera ods for determining inhalation e ticular to the mixing / stirring are to keep the concentrations under limits then respiration protection 	the product and the safe work- tor. m; A3: < 10000 ppm his can be achieved by local Il ventilation. (EN 689 - Meth- xposure). This applies in par- ea. In case this is not sufficent er the occupational exposure

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	paste
Colour	:	white
Odour	:	epoxy-like
Odour Threshold	:	No data available
Flash point	:	> 102 °C
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Lower explosion limit (Vol-%)	:	No data available
Upper explosion limit (Vol-%)	:	No data available
Flammability	:	No data available
Explosive properties	:	No data available



7/14

Sikadur 330 Comp. A

Revision Date 15.02.2020		Version 2.0	Print Date 15.02.2020	
Oxidizing properties	:	No data available		
рН	:	ca. 7 at 500,00 g/l		
Melting point/range / Freez- ing point	:	No data available		
Boiling point/boiling range	:	No data available		
Vapour pressure	:	ca.1 hPa at 20 °C		
Density	:	ca.1,35 g/cm3 at 20 °C		
Water solubility	:	No data available		
Partition coefficient: n- octanol/water	:	No data available		
Viscosity, dynamic	:	No data available		
Viscosity, kinematic	:	> 20,5 mm2/s at 40 °C		
Relative vapour density	:	No data available		
Evaporation rate	:	No data available		
2 Other information No data available				

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

No dangerous reaction known	under conditions of normal use.
10.2 Chemical stability	
The product is chemically stabl	le.
10.3 Possibility of hazardous read	ctions
Hazardous reactions	: Stable under recommended storage conditions.
10.4 Conditions to avoid	
Conditions to avoid	: No data available
10.5 Incompatible materials	
Materials to avoid	: No data available
Country ZA 000000041110	



Sikadur 330 Comp. A

Revision Date 15.02.2020	Version 2.0	Print Date 15.02.2020

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

reaction product: bisphenol weight ≤ 700): Acute oral toxicity	-A-(epichlorhydrin); epoxy resin (number average molecular : LD50 Oral (Rat): > 5.000 mg/kg
Acute dermal toxicity	
1,4-bis(2,3 epoxypropoxy)bu Acute oral toxicity	utane: : LD50 Oral (Rat): 1.163 mg/kg
Hydrocarbons, C10-C13, arc Acute oral toxicity	• •
Acute inhalation toxicity	: LC50 (Rat): > 4,7 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhala- tion toxicity
Skin corrosion/irritation Causes skin irritation.	
Serious eye damage/eye irri Causes serious eye damage.	tation

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction. Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.



Sikadur 330 Comp. A

Revision Date 15.02.2020	Version 2.0	Print Date 15.02.2020

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700):

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 1,8 mg/l Exposure time: 48 h

Hydrocarbons, C10-C13, aromatics, <1% naphthalene:

Toxicity to daphnia and other aquatic invertebrates (Chron- ic toxicity)	EC50: 1,1 mg/l Exposure time: 48 h
ic toxicity)	Species: Daphnia magna (Water flea)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment	: This substance/mixture contains no components considered
	to be either persistent, bioaccumulative and toxic (PBT), or
	very persistent and very bioaccumulative (vPvB) at levels of
	0.1% or higher.

12.6 Other adverse effects

Product:

Additional ecological infor-	: An environmental hazard cannot be excluded in the event of
mation	unprofessional handling or disposal.
	Toxic to aquatic life with long lasting effects.



Sikadur 330 Comp. A

Revision Date 15.02.2020	Version 2.0	Print Date 15.02.2020

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	 The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
European Waste Catalogue	: 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
Contaminated packaging	: 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number	
ADR	: UN 3082
IMDG	: UN 3082
ΙΑΤΑ	: UN 3082
14.2 UN proper shipping name	
ADR	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)
IMDG	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)
ΙΑΤΑ	: Environmentally hazardous substance, liquid, n.o.s. (epoxy resin)
14.3 Transport hazard class(es)	
ADR	: 9



Revision Date 15.02.2020	Version 2.0	Print Date 15.02.2020
IMDG	: 9	
IATA	: 9	
14.4 Packing group		
ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code Transport in accordance with	: 9 : (-)	
IMDG Packing group Labels EmS Code Transport in accordance with :	: III : 9 : F-A, S-F 2.10.2.7 of the IMDG-Code	
IATA Packing instruction (cargo aircraft) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels Transport in accordance with s	: 964 : Y964 : III : Miscellaneous	
14.5 Environmental hazards		
ADR Environmentally hazardous	: yes	
IMDG Marine pollutant	: yes	
14.6 Special precautions for use No data available	r	
14.7 Transport in bulk according Not applicable	to Annex II of MARPOL 73/78 a	and the IBC Code

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3



Revision Date 15.02.2020	Version 2.0		Print Date 15.02.2020
International Chemical Weapons Schedules of Toxic Chemicals an		:	Not applicable
REACH - Candidate List of Subst Concern for Authorisation (Article	ances of Very High	:	None of the components are listed (=> 0.1 %).
REACH - List of substances subje (Annex XIV)		:	Not applicable
Regulation (EC) No 1005/2009 or	n substances that de-	:	Not applicable
plete the ozone layer Regulation (EC) No 850/2004 on lutants	persistent organic pol-	:	Not applicable
Regulation (EC) No 649/2012 of t ment and the Council concerning of dangerous chemicals		:	Not applicable
REACH Information:	All substances contain - registered by our ups - registered by us, and - excluded from the reg - exempted from the reg	strea /or gula	am suppliers, and/or ation, and/or
Seveso III: Directive 2012/18/EU major-accident hazards involving E2			t and of the Council on the control of ARDS
Volatile organic compounds :	(VOCV)		or volatile organic compounds ds (VOC) content: 0,03 %
Directive 2010/75/EU of 24 November 2010 on industria emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 0,03 %, 0,41 g/l VOC content excluding water		ution prevention and control) ds (VOC) content:	

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H304 : H312 : H315 : H317 :	Harmful if swallowed. May be fatal if swallowed and enters airways. Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction. Causes serious eve damage
-	Causes serious eye damage.
	Causes serious eye irritation.
H332 :	Harmful if inhaled.



Revision Date 15.02.2020	Vers	ion 2.0	Print Date 15.02.2020		
H411		: Toxic to aquatic life with long lasting effects.			
H412	: Harmful to ac	: Harmful to aquatic life with long lasting effects.			
Full text of other abbrev	iations				
Acute Tox.		Acute toxicity			
Aquatic Chronic		Long-term (chronic) aquatic hazard			
Asp. Tox.	: Aspiration ha				
Eye Dam.	: Serious eye	damage			
Eye Irrit.	: Eye irritation				
Skin Irrit.	: Skin irritation				
Skin Sens.	: Skin sensitis		a the International Carriage of		
ADR		European Agreement concerning the International Carriage of Dangerous Goods by Road			
CAS		Chemical Abstracts Service			
DNEL		Derived no-effect level			
EC50	: Half maximal	effective concentra	ation		
GHS	: Half maximal	effective concentra	ation		
IATA	: International	Air Transport Asso	ciation		
IMDG		International Maritime Code for Dangerous Goods			
LD50		Median lethal dosis (the amount of a material, given all at			
			50% (one half) of a group of		
	test animals)				
LC50			ncentrations of the chemical in		
		0% of the test anim	als during the observation		
MARPOL	period)	Convention for the	Provention of Pollution from		
MARFOL		 International Convention for the Prevention of Pollution f Ships, 1973 as modified by the Protocol of 1978 			
OEL		l Exposure Limit	101000101 1970		
PBT		oaccumulative and	toxic		
PNEC	-	Predicted no effect concentration			
REACH		Regulation (EC) No 1907/2006 of the European Parliament			
			per 2006 concerning the Reg-		
			on and Restriction of Chemi-		
	cals (REACH	l), establishing a Ει	ropean Chemicals Agency		
SVHC		of Very High Conce			
vPvB	: Very persiste	ent and very bioaccu	umulative		
Classification of the mix	ture:	Classif	ication procedure:		
Skin Irrit. 2	H315		Calculation method		
Eye Dam. 1	H318	-	tion method		
Skin Sens. 1	H317		tion method		
Aquatic Chronic 2	H411	Calcula	tion method		

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



Sikadur 330 Comp. A

Revision Date 15.02.2020

Version 2.0

Print Date 15.02.2020

ZA / EN