According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Sika Concrete Primer B

Revision Date 05.02.2021 Version 1.0 Print Date 05.02.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sika Concrete Primer B

Substance name : 1.3-Cyclohexanedimethanamine. N1.N3-bis(2-

methylpropylidene)

Substance No. : 619-764-7

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Primer

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika South Africa (Pty) Ltd

9 Hocking Place Westmead 3608 Pinetown South Africa

Telephone : +27 (0)31 792 6500
Telefax : +27 (0)31 700 1760
E-mail address of person : headoffice@za.sika.com
responsible for the SDS

1.4 Emergency telephone number

+27 82 490 9409

SECTION 2: Hazards identification

Type of product : Substance

2.1 Classification of the substance or mixture

Classification (SANS 10234)

Skin corrosion, Sub-category 1C H314: Causes severe skin burns and eye damage.

Serious eye damage, Category 1 H318: Causes serious eye damage.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard, Cat- H412: Harmful to aquatic life with long lasting ef-

egory 3 fects.

2.2 Label elements

Labelling (SANS 10234)

Hazard pictograms





According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Sika Concrete Primer B

Version 1.0 Print Date 05.02.2021 Revision Date 05.02.2021

Signal word Danger

Hazard statements H314 Causes severe skin burns and eye damage.

> H317 May cause an allergic skin reaction. H412

Harmful to aquatic life with long lasting ef-

fects.

Prevention: Precautionary statements

> P261 Avoid breathing dust/ fume/ gas/ mist/ va-

pours/ spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immedi-

ately all contaminated clothing. Rinse skin

with water.

P304 + P340 + P310 IF INHALED: Remove person to fresh

air and keep comfortable for breathing. Im-

mediately call a POISON CENTER/ doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a

POISON CENTER/ doctor.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1 Substances

Chemical nature : Amines

Hazardous components

Chemical name	CAS-No. EC-No.	Concentration (% w/w)
1,3- Cyclohexanedimethana- mine, N1,N3-bis(2- methylpropylidene)	173904-11-5 619-764-7	100

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Sika Concrete Primer B

Revision Date 05.02.2021 Version 1.0 Print Date 05.02.2021

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul-

ty.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Allergic reactions

Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Risks : Health injuries may be delayed.

corrosive effects sensitising effects

May cause an allergic skin reaction. Causes serious eye damage.

Causes severe burns.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Sika Concrete Primer B

Print Date 05.02.2021 Revision Date 05.02.2021 Version 1.0

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

5.2 Special hazards arising from the substance or mixture

ucts

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel, Methods for cleaning up

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Do not breathe vapours or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Sika Concrete Primer B

Revision Date 05.02.2021 Version 1.0 Print Date 05.02.2021

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

Smoking, eating and drinking should be prohibited in the application area.

Follow standard hygiene measures when handling chemical

products

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Further information on stor-

age stability

: No decomposition if stored and applied as directed.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
1,3- Cyclohexanedi- methanamine, N1,N3- bis(2- methylpropylidene)	Workers	Inhalation	Long-term systemic effects	17,9 mg/m3
	Workers	Skin contact	Long-term systemic effects	5,07 mg/kg
	Consumers	Inhalation	Long-term systemic effects	3,81 mg/m3
	Consumers	Skin contact	Long-term systemic effects	2,54 mg/kg
	Consumers	Ingestion	Long-term systemic effects	2,54 mg/kg

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Sika Concrete Primer B

Revision Date 05.02.2021 Version 1.0 Print Date 05.02.2021

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
1,3-Cyclohexanedimethanamine,	Fresh water	0,015 mg/l
N1,N3-bis(2-methylpropylidene)		
	Marine water	0,0015 mg/l
	Fresh water sediment	6,6 mg/kg
	Marine sediment	0,66 mg/kg
	Soil	1,23 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water Wear eye/face protection.

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : No special measures required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid
Colour : light yellow
Odour : amine-like
Odour Threshold : No data available

pH : Not applicable

Melting point/range / Freezing :

point

No data available

Boiling point/boiling range : ca. 232 °C

Flash point : 81 °C

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Sika Concrete Primer B

Revision Date 05.02.2021 Version 1.0 Print Date 05.02.2021

Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Self ignition temperature : 239 °C

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : 0,01 hPa

Relative vapour density : ca. 1

Density : ca. 0,9 g/cm3 (20 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : $> 7 \text{ mm2/s} (40 \degree \text{C})$

Explosive properties : No data available

Oxidizing properties : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Sika Concrete Primer B

Revision Date 05.02.2021 Version 1.0 Print Date 05.02.2021

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

1,3-Cyclohexanedimethanamine, N1,N3-bis(2-methylpropylidene):

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Sika Concrete Primer B

Revision Date 05.02.2021 Version 1.0 Print Date 05.02.2021

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

Components:

1,3-Cyclohexanedimethanamine, N1,N3-bis(2-methylpropylidene):

Toxicity to fish : LC50 (Fish): 68,79 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia (water flea)): 68,79 mg/l

Exposure time: 48 h

Toxicity to algae : (Desmodesmus subspicatus (green algae)): 14,8 mg/l

Exposure time: 72 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Other adverse effects

Product:

Additional ecological infor-

mation

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Sika Concrete Primer B

Revision Date 05.02.2021 Version 1.0 Print Date 05.02.2021

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

European Waste Catalogue : 08 01 11* waste paint and varnish containing organic sol-

vents or other dangerous substances

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated

by dangerous substances

SECTION 14: Transport information

14.1 UN number

 ADR
 : UN 3066

 IMDG
 : UN 3066

 IATA
 : UN 3066

14.2 UN proper shipping name

ADR : PAINT RELATED MATERIAL IMDG : PAINT RELATED MATERIAL

IATA : Paint related material

14.3 Transport hazard class(es)

 ADR
 : 8

 IMDG
 : 8

 IATA
 : 8

14.4 Packing group

ADR

Packing group : III
Classification Code : C9
Hazard Identification Number : 80
Labels : 8
Tunnel restriction code : (E)

Remarks : Transport according to chapter 3.4 (LQ) possible

IMDG

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Sika Concrete Primer B

Revision Date 05.02.2021 Version 1.0 Print Date 05.02.2021

Ш Packing group Labels 8

EmS Code F-A. S-B Remarks Alkalis

IATA (Cargo)

Packing instruction (cargo 856

aircraft)

Packing instruction (LQ) Y841 Packing group Ш Labels Corrosive

IATA (Passenger)

Packing instruction (passen-852

ger aircraft)

Packing instruction (LQ) Y841 Packing group Ш

Labels Corrosive

14.5 Environmental hazards

ADR

Environmentally hazardous no

Marine pollutant no

IATA (Passenger)

Environmentally hazardous no

IATA (Cargo)

Environmentally hazardous no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances. preparations and articles (Annex XVII)

Conditions of restriction for the following entries should be considered: Number on list 3

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).

: Not applicable

None of the components are listed

(=> 0.1 %).

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Sika Concrete Primer B

Revision Date 05.02.2021 Version 1.0 Print Date 05.02.2021

REACH - List of substances subject to authorisation : Not applicable

(Annex XIV)

Regulation (EC) No 1005/2009 on substances that de- : Not applicable

plete the ozone layer

Regulation (EU) 2019/1021 on persistent organic pollu- : Not applicable

tants (recast)

Regulation (EC) No 649/2012 of the European Parlia: Not applicable

ment and the Council concerning the export and import

of dangerous chemicals

REACH Information: All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

excluded from the regulation, and/orexempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV) no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)

Not applicable

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for this substance by the supplier.

SECTION 16: Other information

Full text of other abbreviations

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road : Chemical Abstracts Service

CAS : Chemical Abstracts Ser DNEL : Derived no-effect level

EC50 : Half maximal effective concentration GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



Sika Concrete Primer B

Revision Date 05.02.2021 Version 1.0 Print Date 05.02.2021

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

ZA / EN