

SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



SikaGrout®-3200 ZA

Revision Date 27.02.2019

Version 1.0

Print Date 27.02.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SikaGrout®-3200 ZA

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Grouting mortar

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika South Africa (Pty) Ltd
9 Hocking Place
Westmead
3608 Pinetown
South Africa

Telephone : +27 (0)31 792 6500
Telefax : +27 (0)31 700 1760
E-mail address of person responsible for the SDS : headoffice@za.sika.com

1.4 Emergency telephone number

+27 82 490 9409

SECTION 2: Hazards identification

Type of product : Mixture

2.1 Classification of the substance or mixture

Classification (SANS 10234)

Skin irritation, Category 2 H315: Causes skin irritation.

Serious eye damage, Category 1 H318: Causes serious eye damage.

Specific target organ toxicity - single exposure, Category 3, Respiratory system H335: May cause respiratory irritation.

2.2 Label elements

Labelling (SANS 10234)

Hazard pictograms :



Signal word : Danger

SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



SikaGrout®-3200 ZA

Revision Date 27.02.2019

Version 1.0

Print Date 27.02.2019

| | | |
|--------------------------|--|---|
| Hazard statements | : H315 H318 H335 | Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. |
| Precautionary statements | : Prevention: P261 P264 P280 | Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Wear protective gloves/ eye protection/ face protection. |
| | : Response: P304 + P340 + P312 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. |
| | : P305 + P351 + P338 + P310 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. |
| | : Storage: P403 + P233 | Store in a well-ventilated place. Keep container tightly closed. |

Hazardous components which must be listed on the label:
Cement (chromium reduced)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

The content of soluble Chromium (VI) is not greater than 0,0002% in accordance with Annex XVII, Paragraph 47 of the EU Regulation 1907/2006.

The product reacts highly alkaline with water.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

| Chemical name | CAS-No. EC-No. Registration number | Classification (SANS 10234) | Concentration (% w/w) |
|--|--|---|--------------------------|
| Cement (chromium reduced) | 65997-15-1 266-043-4 | Skin Irrit.2; H315 Eye Dam.1; H318 STOT SE3; H335 | >= 40 - < 60 |
| Substances with a workplace exposure limit : | | | |
| Quartz (SiO ₂) | 14808-60-7 | | >= 40 - < 60 |

SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



SikaGrout®-3200 ZA

Revision Date 27.02.2019

Version 1.0

Print Date 27.02.2019

| | | | |
|---------------|---|--|--------------|
| Fumes, silica | 238-878-4 69012-64-2 273-761-1 01-2119486866-17-XXXX | | >= 1 - < 2,5 |
|---------------|---|--|--------------|

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
- If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Cough
Respiratory disorder
Excessive lachrymation
Erythema
Dermatitis
See Section 11 for more detailed information on health effects and symptoms.
- Risks : irritant effects
Causes skin irritation.
Causes serious eye damage.

SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



SikaGrout®-3200 ZA

Revision Date 27.02.2019

Version 1.0

Print Date 27.02.2019

May cause respiratory irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Try to prevent the material from entering drains or water courses.
No special environmental precautions required.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Pick up and arrange disposal without creating dust.
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



SikaGrout®-3200 ZA

Revision Date 27.02.2019

Version 1.0

Print Date 27.02.2019

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Do not breathe vapours/dust.
Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Store in original container. Keep in a well-ventilated place. Observe label precautions. Store in accordance with local regulations.
- Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

- Specific use(s) : Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|----------------------------|-------------------|-------------------------------|-----------------------|------------|
| Quartz (SiO ₂) | 14808-60-7 | TWA OEL-CL (Respirable dust) | 0,1 mg/m ³ | ZA OEL |
| Further information | Control Limit | | | |
| | | TWA OEL-RL (Respirable dust) | 0,1 mg/m ³ | ZA OEL |
| Further information | Recommended Limit | | | |
| | | TWA (Respirable dust) | 0,1 mg/m ³ | 2004/37/EC |

SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



SikaGrout®-3200 ZA

Revision Date 27.02.2019

Version 1.0

Print Date 27.02.2019

| | | | | |
|---------------------------|-------------------------|------------------------------|----------------------|--------|
| Further information | Carcinogens or mutagens | | | |
| Cement (chromium reduced) | 65997-15-1 | TWA OEL-RL (Respirable dust) | 5 mg/m ³ | ZA OEL |
| Further information | Recommended Limit | | | |
| | | TWA OEL-RL (inhalable dust) | 10 mg/m ³ | ZA OEL |
| Further information | Recommended Limit | | | |
| Fumes, silica | 69012-64-2 | TWA OEL-RL (Respirable dust) | 3 mg/m ³ | ZA OEL |
| Further information | Recommended Limit | | | |
| | | TWA OEL-RL (inhalable dust) | 6 mg/m ³ | ZA OEL |
| Further information | Recommended Limit | | | |

8.2 Exposure controls

Personal protective equipment

- Eye protection : Safety glasses with side-shields conforming to EN166
Eye wash bottle with pure water
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
- Recommended: Butyl rubber/nitrile rubber gloves.
Contaminated gloves should be removed.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : solid

SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



SikaGrout®-3200 ZA

Revision Date 27.02.2019

Version 1.0

Print Date 27.02.2019

| | | |
|--|---|-----------------------|
| Colour | : | grey |
| Odour | : | No data available |
| Odour Threshold | : | No data available |
| Flash point | : | No data available |
| Autoignition temperature | : | No data available |
| Decomposition temperature | : | No data available |
| Lower explosion limit (Vol-%) | : | No data available |
| Upper explosion limit (Vol-%) | : | No data available |
| Flammability | : | No data available |
| Explosive properties | : | No data available |
| Oxidizing properties | : | No data available |
| pH | : | No data available |
| Melting point/range / Freezing point | : | No data available |
| Boiling point/boiling range | : | No data available |
| Vapour pressure | : | No data available |
| Density | : | 2,3 g/cm ³ |
| Water solubility | : | No data available |
| Partition coefficient: n-octanol/water | : | No data available |
| Viscosity, dynamic | : | No data available |
| Viscosity, kinematic | : | No data available |
| Relative vapour density | : | No data available |
| Evaporation rate | : | No data available |

9.2 Other information

No data available

SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



SikaGrout®-3200 ZA

Revision Date 27.02.2019

Version 1.0

Print Date 27.02.2019

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



SikaGrout®-3200 ZA

Revision Date 27.02.2019

Version 1.0

Print Date 27.02.2019

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Additional ecological information : There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



SikaGrout®-3200 ZA

Revision Date 27.02.2019

Version 1.0

Print Date 27.02.2019

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

No data available

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



SikaGrout®-3200 ZA

Revision Date 27.02.2019

Version 1.0

Print Date 27.02.2019

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Cement (chromium reduced) (47)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H315 : Causes skin irritation.
H318 : Causes serious eye damage.
H335 : May cause respiratory irritation.

Full text of other abbreviations

Eye Dam. : Serious eye damage
Skin Irrit. : Skin irritation
STOT SE : Specific target organ toxicity - single exposure
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS : Chemical Abstracts Service
DNEL : Derived no-effect level
EC50 : Half maximal effective concentration
GHS : Half maximal effective concentration
IATA : International Air Transport Association
IMDG : International Maritime Code for Dangerous Goods
LD50 : Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50 : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL : Occupational Exposure Limit
PBT : Persistent, bioaccumulative and toxic
PNEC : Predicted no effect concentration
REACH : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC : Substances of Very High Concern
vPvB : Very persistent and very bioaccumulative

SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



SikaGrout®-3200 ZA

Revision Date 27.02.2019

Version 1.0

Print Date 27.02.2019

Classification of the mixture:

| | |
|---------------|------|
| Skin Irrit. 2 | H315 |
| Eye Dam. 1 | H318 |
| STOT SE 3 | H335 |

Classification procedure:

| |
|--------------------|
| Calculation method |
| Calculation method |
| Calculation method |

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

ZA / EN