

PRODUCT DATA SHEET

SikaForce®-096 Cleaner

Cleaning liquid for tools and application equipment

TYPICAL PRODUCT DATA (FURTHER VALUES SEE SAFETY DATA SHEET)

Chemical base	Dipropylene glycol ether
Color	Colorless
Density	0.97 kg/l
Viscosity Rheometer, CC25, shear rate 50 s ⁻¹	3.5 mPa·s ^A
Vapor pressure	0.4 mm Hg/25 °C
Boiling point	190 °C
Flash-point	79 °C
Shelf life	24 months

CQP = Corporate Quality Procedure

A) 25 °C

DESCRIPTION

SikaForce®-096 Cleaner is a liquid cleaning agent with high boiling point, designed for removing non-cured SikaForce® polyurethane adhesives from tools and application equipment.

PRODUCT BENEFITS

- Not classified
- Safe to use
- Neutralizes the isocyanate groups in polyurethane products

AREAS OF APPLICATION

SikaForce®-096 Cleaner is used for cleaning of tools and flushing of application equipment after dispensing SikaForce® adhesives. This product is suitable for experienced professional users only.

METHOD OF APPLICATION

Uncured 1- and 2-component SikaForce® products can be removed from tools and application equipment with SikaForce®-096 Cleaner.

Provide adequate ventilation. If SikaForce®-096 Cleaner is processed at temperatures > 30 °C use a local extraction system.

Clean tools by using a brush. If necessary, immerse parts in the SikaForce®-096 Cleaner prior the cleaning process.

For 2-component equipment, it is recommended flushing with recirculation.

STORAGE CONDITIONS

SikaForce®-096 Cleaner has to be kept between 10 °C and 30 °C in a tightly closed packaging and stored in a well-ventilated storage room.

FURTHER INFORMATION

The information herein is offered for general guidance only. Advice on specific applications is available on request from the Technical Department of Sika Industry.

Copies of the following publications are available on request:

- Safety Data Sheets

BASIS OF PRODUCT DATA

All technical data stated in this document are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

HEALTH AND SAFETY INFORMATION

For information and advice regarding transportation, handling, storage and disposal of chemical products, users shall refer to the actual Safety Data Sheets containing physical, ecological, toxicological and other safety-related data.

DISCLAIMER

The information, and, in particular, the recommendations relating to the application and end use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.