

PRODUCT DATA SHEET

Sika® Separol GU ZA

Oil based shutter release agent

DESCRIPTION

Sika® Separol GU ZA is an oil based release agent formulated to provide easy release properties to formwork and a high quality surface finish.

USES

Sika® Separol GU ZA, when applied to steel, plastic or timber formwork allows clean, fast and easy striking.

CHARACTERISTICS / ADVANTAGES

Sika® Separol GU ZA provides the following beneficial properties:

- Suitable for use on wood, metals and plastic
- Allows clean, easy striking
- Improved finish for fair faced concrete
- Reduces concrete contamination
- Economical coverage rates

PRODUCT INFORMATION

Chemical Base	Oil based agent
Packaging	25 and 200 litre drums.
Appearance / Colour	Brownish yellow liquid
Shelf Life	12 months from date of production
Storage Conditions	Store properly in original unopened, undamaged, sealed packaging. Protect from frost, direct sunlight and contamination. Opened units should be stored closed.
Density	0,85 kg/litre
Consumption	Timber : <ul style="list-style-type: none"> ▪ approx. 25 sq. meters per litre depending on porosity. Steel or plastic: <ul style="list-style-type: none"> ▪ approx. 50 sq. meters per litre depending on surface texture and porosity.
Ambient Air Temperature	Min.5°C - Max.35°C

APPLICATION INSTRUCTIONS

APPLICATION

Thin layer thickness

LIMITATIONS

Contact with skin and eyes must be avoided. Residues of material must be removed according to local regulations. Fully cured material can be disposed of as household waste under agreement with the responsible local authorities. Detailed health and safety information as well as detailed precautionary measures e.g. physical, toxicological and ecological data can be obtained from the Material Safety Data Sheet.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

ECOLOGY HEALTH AND SAFETY

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request. It may be necessary to adapt the above disclaimer to specific local laws and regulations. Any changes to this disclaimer may only be implemented with permission of Sika® Corporate Legal in Baar.

Sika South Africa (Pty) Ltd
9 Hocking Place,
Westmead, 3608
South Africa
Phone +27 31 792 6500
www.sika.co.za



Product Data Sheet
Sika® Separol GU ZA
August 2020, Version 01.02
021405021000000313

SikaSeparolGUZA-en-ZA-(08-2020)-1-2.pdf