

PRODUCT DATA SHEET

Sika® Separol®-302

(formerly MasterFinish® 302)

High performance chemical and physical mould release agent

DESCRIPTION

Sika® Separol®-302 is a multi-purpose chemical release agent for all types of shutters. It is mineral oil based and will produce satisfactory results on concrete surfaces under all construction and manufacturing conditions. Application by spray is recommended.

USES

Sika® Separol®-302 may be used for all general applications and is especially reliable for achieving high quality off-shutter finishes.

The use of specific mould releasing aids should always be determined by site trials. Oils should not be used on rubber or plastic moulds. Waxes are especially suited for non-absorbing shutters as a base preparation and chemical sensitive moulding materials such as plastic and rubber.

CHARACTERISTICS / ADVANTAGES

Sika® Separol®-302 is mineral oil based and will produce satisfactory results on concrete surfaces under all construction and manufacturing conditions.

PRODUCT INFORMATION

Packaging	Sika® Separol®-302 is available in 20 litre or 210 litre drums.
Shelf Life	12 months from date of manufacture when stored in undamaged, unopened packaging.
Storage Conditions	Store under cover, out of direct sunlight and protect from extremes of temperatures. Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging.

Appearance / Colour Brownish liquid

Density 0.90

TECHNICAL INFORMATION

Specific Advice

Apply before the first casting and thereafter reapply immediately after stripping and cleaning the mould. Lightweight horticultural sprayers are ideal as Sika® Separol®-302 is finely atomized to give a uniform coating. Excessive application should be avoided. Alternatively, application may be made by a fine haired brush, only a very thin coating should be made, and any excess removed.

Substrate

Coverage 25 - 35 m³/l

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY HEALTH AND SAFETY

Please consult the Safety Data Sheet (SDS) for detailed information

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika South Africa (Pty) Ltd

9 Hocking Place,
Westmead, 3608
South Africa
Phone +27 31 792 6500
www.sika.co.za



Product Data Sheet

Sika® Separol®-302
October 2023, Version 01.01
021405000000002133

SikaSeparol-302-en-ZA-(10-2023)-1-1.pdf