

PRODUCT DATA SHEET

Sika® Plasterstik

Cement mortar bonding liquid

DESCRIPTION

Sika® Plasterstik is a co-polymer emulsion specially formulated to improve the adhesion of cement mortars to substrates

USES

Sika® Plasterstik is used to provide an excellent low cost bonding agent for cement plasters and renders

CHARACTERISTICS / ADVANTAGES

- Water based
- Easy to use
- Economical
- Non-toxic

PRODUCT INFORMATION

Packaging	5 and 25ltr containers
Appearance / Colour	White liquid
Shelf Life	12 months from date of production
Storage Conditions	Store properly in undamaged and unopened original sealed packaging in dry and cool conditions between 5°C - 30°C. Liquid must be protected from frost.
Density	1.01kg/ltr
pH-Value	4.5
Consumption	6 - 10m ² per litre. Coverage figures depend on the surface texture and porosity of the substrate
Ambient Air Temperature	Min. 5°C – max. 30°C
Substrate Temperature	Min. 5°C – max. 35°C

SUBSTRATE QUALITY / PRE-TREATMENT

The brick /concrete shall be thoroughly clean, free from dust, loose material, surface contamination and materials which reduce bond or prevent suction or wetting by repair materials

MIXING

Sika® Plasterstik is supplied ready to use, just stir before using

APPLICATION METHOD / TOOLS

Apply a coat of Sika® Plasterstik by brush or roller. Whilst the Sika® Plasterstik is still tacky apply the cement plaster or render in the normal way.

LIMITATIONS

Sika® Plasterstik must not be diluted

Sika® Plasterstik should not be used where it will be in permanent contact with water or below ground level. For these applications use Sikalatex

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

ECOLOGY HEALTH AND SAFETY

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request. It may be necessary to adapt the above disclaimer to specific local laws and regulations. Any changes to this disclaimer may only be implemented with permission of Sika® Corporate Legal in Baar.

Sika South Africa (Pty) Ltd

9 Hocking Place,
Westmead, 3608
South Africa
Phone +27 31 792 6500
www.sika.co.za



Product Data Sheet

Sika® Plasterstik
August 2020, Version 01.03
020301010010000119

SikaPlasterstik-en-ZA-(08-2020)-1-3.pdf