

Revision Date 25.03.2021	Version 1.0	Print Date 25.03.2021

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product	identifier
-------------	------------

Trade name

Sikafloor -3240 (B)

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use		Polyurethane coating
	-	I oryuremane coaling

### 1.3 Details of the supplier of the safety data sheet

Company name of supplier	: Sika South Africa (Pty) Ltd 9 Hocking Place
	Westmead
	3608 Pinetown
	South Africa
Telephone	: +27 (0)31 792 6500
Telefax	: +27 (0)31 700 1760
E-mail address of person responsible for the SDS	: headoffice@za.sika.com

#### 1.4 Emergency telephone number

+27 82 490 9409

## **SECTION 2: Hazards identification**

Type of product

: Mixture

## 2.1 Classification of the substance or mixture

## **Classification (SANS 10234)**

Acute toxicity, Category 4 Skin irritation, Category 2 Eye irritation, Category 2 Respiratory sensitisation, Category 1

Skin sensitisation, Category 1 Carcinogenicity, Category 2 Specific target organ toxicity - single exposure, Category 3, Respiratory system Specific target organ toxicity - repeated exposure, Category 2

#### 2.2 Label elements

Labelling (SANS 10234)

H332: Harmful if inhaled.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317: May cause an allergic skin reaction.

H351: Suspected of causing cancer.

H335: May cause respiratory irritation.

H373: May cause damage to organs through prolonged or repeated exposure.



# Sikafloor -3240 (B)

Revision Date 25.03.2021	Version	1.0	Print Date 25.03.2021
Hazard pictograms		<b>?</b>	
Signal word	Danger	<b>V</b>	
Hazard statements	H315 H317 H319 H332 H334 H335 H351 H373	breathing difficultie May cause respirat Suspected of caus	rgic skin reaction. e irritation. or asthma symptoms or es if inhaled. tory irritation. ing cancer. e to organs through pro-
Precautionary statements	Prevention:           P201           P260           P264           P280           Response:           P304 + P340 + P	Do not breathe dus pours/ spray. Wash skin thoroug Wear protective glo eye protection/ fact tection. 312 IF INHALED: air and keep comfo	ructions before use. st/ fume/ gas/ mist/ va- hly after handling. oves/ protective clothing/ e protection/ hearing pro- Remove person to fresh ortable for breathing. Call R/ doctor if you feel un-
	P308 + P313	well.	cerned: Get medical ad-

Hazardous components which must be listed on the label: Diphenylmethanediisocyanate, isomeres and homologues methylenediphenyl diisocyanate

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## **SECTION 3: Composition/information on ingredients**

## 3.2 Mixtures

#### Hazardous components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.	(SANS 10234)	(% w/w)



# Sikafloor -3240 (B)

Revision Date 25.03.2021	Version 1.0	Print Date 25.03.2021

	Registration number		
methylenediphenyl diisocyanate	26447-40-5 01-2119457015-45- XXXX	Acute Tox.4; H332 Skin Irrit.2; H315 Eye Irrit.2; H319 Resp. Sens.1; H334 Skin Sens.1; H317 Carc.2; H351 STOT SE3; H335 STOT RE2; H373	>= 40 - < 60
Diphenylmethanediisocyanate, iso- meres and homologues	9016-87-9	Acute Tox.4; H332 Skin Irrit.2; H315 Eye Irrit.2; H319 Resp. Sens.1; H334 Skin Sens.1; H317 Carc.2; H351 STOT SE3; H335 STOT RE2; H373	>= 40 - < 60

For explanation of abbreviations see section 16.

## **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	:	Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.

#### 4.2 Most important symptoms and effects, both acute and delayed

Country ZA 10000008956

: Asthmatic appearance



# Sikafloor -3240 (B)

Revision Date 25.03.2021	Version 1.0	Print Date 25.03.2021
	Cough Respiratory disorder Allergic reactions Excessive lachrymation Erythema Headache Dermatitis See Section 11 for more detailed inform and symptoms.	nation on health effects
Risks :	irritant effects sensitising effects Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptom ties if inhaled. May cause respiratory irritation. Suspected of causing cancer. May cause damage to organs through exposure.	
4.3 Indication of any immediate me	dical attention and special treatment r	needed
Treatment :	Treat symptomatically.	
SECTION 5: Firefighting measur	es	
5.1 Extinguishing media		
Suitable extinguishing media :	In case of fire, use water/water spray/w ide/sand/foam/alcohol resistant foam/c extinction.	
5.2 Special hazards arising from the	e substance or mixture	
Hazardous combustion prod- : ucts	No hazardous combustion products are	e known

## 5.3 Advice for firefighters

Special protective equipment for firefighters	: In the event of fire, wear self-contained breathing apparatus.
Further information	: Standard procedure for chemical fires.



Sikafloor -3240 (B)

Revision Date 25.03.2021	Version 1.0	Print Date 25.03.2021
SECTION 6: Accidental release	measures	

• •	e equipment and emergency procedures Use personal protective equipment. Deny access to unprotected persons.
6.2 Environmental precautions	
Environmental precautions :	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3 Methods and material for contai	nment and cleaning up
Methods for cleaning up :	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For personal protection see section 8.

## **SECTION 7: Handling and storage**

## 7.1 Precautions for safe handling

Advice on safe handling :	Avoid formation of aerosol.
	Avoid exceeding the given occupational exposure limits (see section 8).
	Do not get in eyes, on skin, or on clothing.
	For personal protection see section 8.
	Persons with a history of skin sensitisation problems or asth-
	ma, allergies, chronic or recurrent respiratory disease should
	not be employed in any process in which this mixture is being used.
	Smoking, eating and drinking should be prohibited in the application area.
	Provide sufficient air exchange and/or exhaust in work rooms. Follow standard hygiene measures when handling chemical products
Advice on protection against : fire and explosion	Normal measures for preventive fire protection.
Hygiene measures :	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2 Conditions for safe storage, inc	luding any incompatibilities

## Requirements for storage : Keep container tightly closed in a dry and well-ventilated



Revision Date 25.03.2021		Version 1.0	Print Date 25.03.2021
areas and containers		place. Containers which are open sealed and kept upright to preven ance with local regulations.	
Further information on stor- age stability	:	No decomposition if stored and ap	oplied as directed.
7.3 Specific end use(s)			

## **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

## Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Diphenylme- thanediisocyanate, isomeres and homologues	9016-87-9	TWA OEL-CL	0,02 mg/m3 (Cyanide)	ZA OEL
	Further information: Control Limit, Sensitisers that may cause sensitisation by inhalation			
		STEL OEL-CL	0,07 mg/m3 (Cyanide)	ZA OEL
methylenediphenyl diisocyanate	26447-40-5	TWA OEL-RL	0,02 mg/m3	ZA OEL
	Further information: Sensitisers that may cause sensitisation by inhalation, Recommended Limit			
		STEL OEL-RL	0,07 mg/m3	ZA OEL

#### 8.2 Exposure controls

#### Personal protective equipment

Eye protection	: Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water	
Hand protection	: Chemical-resistant, impervious gloves complying with a proved standard must be worn at all times when handlir chemical products. Reference number EN 374. Follow r facturer specifications.	ng
	Suitable for short time use or protection against splashe Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.	}S:
Skin and body protection	<ul> <li>Protective clothing (e.g. Safety shoes acc. to EN ISO 20 long-sleeved working clothing, long trousers). Rubber a and protective boots are additionaly recommended for r</li> </ul>	prons



Revision Date 25.03.2021	Version 1.0	Print Date 25.03.2021
	and stirring work.	
Respiratory protection :	In case of inadequate ventilation wear Respirator selection must be based on exposure levels, the hazards of the pro- ing limits of the selected respirator. Use a properly fitted NIOSH approved respirator complying with an approved sessment indicates this is necessary. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: Ensure adequate ventilation. This can exhaust extraction or by general ventila ods for determining inhalation exposur- ticular to the mixing / stirring area. In ca to keep the concentrations under the o limits then respiration protection measur- Ensure adequate ventilation, especially	known or anticipated oduct and the safe work- air-purifying or air-fed standard if a risk as- < 10000 ppm be achieved by local ation. (EN 689 - Meth- e). This applies in par- ase this is not sufficent ccupational exposure ures must be used.

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Information on basic physical and chemical properties			
Appearance Colour Odour	:	liquid light brown musty	
Odour Threshold	:	No data available	
рН	:	Not applicable substance/mixture is non-soluble (in water)	
Melting point/range / Freezing point	:		
Boiling point/boiling range	:	No data available	
Flash point	:	> 150 °C Method: open cup	
Evaporation rate	:	No data available	
Flammability (solid, gas)	:	No data available	
Upper explosion limit / Upper flammability limit	:	No data available	
Lower explosion limit / Lower flammability limit	:	No data available	
Vapour pressure	:	0,01 hPa	
Relative vapour density	:	No data available	



Revision Date 25.03.2021		Version 1.0	Print Date 25.03.2021
Density	:	ca. 1,18 g/cm3 (20 °C)	
Solubility(ies) Water solubility Solubility in other solvents	:	insoluble No data available	
Partition coefficient: n-	:	No data available	
octanol/water Auto-ignition temperature	:	No data available	
Decomposition temperature	:	No data available	
Viscosity Viscosity, dynamic	:	70 - 90 mPa.s (20 °C)	
Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)	
Explosive properties	:	No data available	
Oxidizing properties	:	No data available	
<b>9.2 Other information</b> No data available			
SECTION 10: Stability and rea	icti	vity	
<ul> <li>10.1 Reactivity</li> <li>No dangerous reaction known under conditions of normal use.</li> <li>10.2 Chemical stability</li> </ul>			
The product is chemically stab			
<b>10.3 Possibility of hazardous rea</b> Hazardous reactions	Ctio	ons No hazards to be specially mentioned.	

### 10.4 Conditions to avoid

Conditions to avoid :		No data available
-----------------------	--	-------------------

## 10.5 Incompatible materials

Materials to avoid : No da	ata available
----------------------------	---------------

#### **10.6 Hazardous decomposition products**

No decomposition if stored and applied as directed.



## Sikafloor -3240 (B)

Revision Date 25.03.2021

Version 1.0

Print Date 25.03.2021

## **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

#### Acute toxicity

Harmful if inhaled.

#### Components:

#### Diphenylmethanediisocyanate, isomeres and homologues:

- Acute oral toxicity : LD50 Oral (Rat): > 10.000 mg/kg
- Acute inhalation toxicity : LC50: 1,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement Assessment: The component/mixture is moderately toxic after short term inhalation.
- Acute dermal toxicity : LD50 Dermal (Rabbit): > 9.400 mg/kg

### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

Causes serious eye irritation.

### Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction. Respiratory sensitisation: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Suspected of causing cancer.

#### **Reproductive toxicity**

Not classified based on available information.

#### STOT - single exposure

May cause respiratory irritation.

#### STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

#### **Aspiration toxicity**

Not classified based on available information.



# Sikafloor -3240 (B)

Revision Date 25.03.2021

Version 1.0

Print Date 25.03.2021

## **SECTION 12: Ecological information**

## 12.1 Toxicity

<u>Components:</u> Diphenylmethanediisocyanate,	isomeres and homologues:
• •	LC50 (Brachydanio rerio (zebrafish)): > 1.000 mg/l Exposure time: 96 h
Toxicity to algae :	EC50 (Desmodesmus subspicatus (green algae)): > 1.640 mg/l Exposure time: 72 h
12.2 Persistence and degradability	
No data available	
12.3 Bioaccumulative potential	
No data available	
12.4 Mobility in soil	
No data available	
12.5 Results of PBT and vPvB asse	ssment
Product:	
Assessment :	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
12.6 Other adverse effects	
Product:	
Additional ecological infor- : mation	There is no data available for this product.

## **SECTION 13: Disposal considerations**

13.1 Waste treatment methods	
Product	: The generation of waste should be avoided or minimized wherever possible.
	Empty containers or liners may retain some product residues.
	This material and its container must be disposed of in a safe way.
	Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
	Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental



Revision Date 25.03.2021	Version 1.0	Print Date 25.03.2021	
	protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.		
European Waste Catalogue	: 08 05 01* waste isocyanates		
Contaminated packaging	: 15 01 10* packaging containing by dangerous substances	residues of or contaminated	

## **SECTION 14: Transport information**

#### 14.1 UN number

Not regulated as a dangerous good

#### 14.2 UN proper shipping name

Not regulated as a dangerous good

### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

#### 14.4 Packing group

Not regulated as a dangerous good

### 14.5 Environmental hazards

Not regulated as a dangerous good

#### 14.6 Special precautions for user

Not applicable

# 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

## **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 3
		Diphenylmethanediisocyanate, iso- meres and homologues (Number on list 56) methylenediphenyl diisocyanate (Number on list 56)
International Chemical Weapons Convention (CWC)	:	Not applicable



Sikafloor -3240 (B)

Revision Date 25.03.2021	Version 1.0	Print Date 25.03.2021	
Schedules of Toxic Chemicals an REACH - Candidate List of Subs Concern for Authorisation (Article REACH - List of substances subj (Annex XIV) Regulation (EC) No 1005/2009 of plete the ozone layer Regulation (EU) 2019/1021 on p tants (recast) Regulation (EC) No 649/2012 of ment and the Council concerning of dangerous chemicals REACH Information:	tances of Very High e 59). ject to authorisation on substances that de- ersistent organic pollu- the European Parlia- g the export and import All substances contain	gulation, and/or	
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. Not applicable			
Volatile organic compounds :	Law on the incentive ta (VOCV) no VOC duties	ax for volatile organic compounds	
		of 24 November 2010 on industrial pollution prevention and control)	

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

## **SECTION 16: Other information**

Full text of H-Statements	
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H334	: May cause allergy or asthma symptoms or breathing difficul- ties if inhaled.
H335	: May cause respiratory irritation.
H351	: Suspected of causing cancer.
H373	: May cause damage to organs through prolonged or repeated exposure.

#### Full text of other abbreviations

Acute Tox.	: Acute toxicity	
Country 7A 10000000000		10/14



# Sikafloor -3240 (B)

Revision Date 25.03.2021	Vers	ion 1.0	Print Date 25.03.2021
Carc.	: Carcinogenio	city	
Eye Irrit.	: Eye irritation		
Resp. Sens.	: Respiratory		
Skin Irrit.	: Skin irritation	n	
Skin Sens.	: Skin sensitis	ation	
STOT RE	: Specific targ	Specific target organ toxicity - repeated exposure	
STOT SE	: Specific targ	Specific target organ toxicity - single exposure	
ADR	: European Ag	: European Agreement concerning the International Carriage	
	Dangerous C	Goods by Road	
CAS	: Chemical Ab	stracts Service	
DNEL	: Derived no-e		
EC50		I effective concentra	ation
GHS		Globally Harmonized System	
IATA		Air Transport Asso	
IMDG		Maritime Code for	
LD50			of a material, given all at
			f 50% (one half) of a group of
	test animals)		
LC50			ncentrations of the chemical in
		50% of the test anim	nals during the observation
	period)		
MARPOL			Prevention of Pollution from
		Ships, 1973 as modified by the Protocol of 1978	
OEL		: Occupational Exposure Limit	
PBT	,	Persistent, bioaccumulative and toxic	
PNEC		Predicted no effect concentration	
REACH	<ul> <li>Regulation (EC) No 1907/2006 of the European Parlian and of the Council of 18 December 2006 concerning the</li> </ul>		
			on and Restriction of Chemi- uropean Chemicals Agency
SVHC		of Very High Conce	
vPvB		ent and very bioacci	
	. Very persiste	ent and very bloace	
Classification of the mixt	ure:	Classif	ication procedure:
Acute Tox. 4	H332	Calcula	tion method
Skin Irrit. 2	H315		ition method
SKIII IIIII. Z	п <b>э</b> тэ	Calcula	

	11002	Calculation motified
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Resp. Sens. 1	H334	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 2	H351	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



Sikafloor -3240 (B)

Revision Date 25.03.2021

Version 1.0

Print Date 25.03.2021

ZA / EN