

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikafloor®-235 ESD (A)

Revision Date 07.09.2020

Version 1.0

Print Date 07.09.2020

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Sikafloor®-235 ESD (A)

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Epoxy coating

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika South Africa (Pty) Ltd  
9 Hocking Place  
Westmead  
3608 Pinetown  
South Africa  
Telephone : +27 (0)31 792 6500  
Telefax : +27 (0)31 700 1760  
E-mail address of person responsible for the SDS : headoffice@za.sika.com

#### 1.4 Emergency telephone number

+27 82 490 9409

### SECTION 2: Hazards identification

Type of product : Mixture

#### 2.1 Classification of the substance or mixture

##### Classification (SANS 10234)

Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (SANS 10234)

Hazard pictograms :



Signal word : Warning

Hazard statements : H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikafloor®-235 ESD (A)

Revision Date 07.09.2020

Version 1.0

Print Date 07.09.2020

	H319	Causes serious eye irritation.
	H411	Toxic to aquatic life with long lasting effects.
Precautionary statements	<b>Prevention:</b>	
	P261	Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
	P264	Wash skin thoroughly after handling.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/ eye protection/ face protection.
	<b>Response:</b>	
	P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
	P391	Collect spillage.

Hazardous components which must be listed on the label:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq$  700)

reaction product: bisphenol F-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq$  700)

p-tert-butylphenyl 1-(2,3-epoxy)propyl ether

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (SANS 10234)	Concentration (% w/w)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700)	25068-38-6  01-2119456619-26-XXXX	Eye Irrit.2; H319 Skin Irrit.2; H315 Skin Sens.1; H317 Aquatic Chronic2; H411	$\geq$ 20 - < 25
reaction product: bisphenol F-(epichlorhydrin) epoxy resin (number average molecular weight $\leq$ 700)	9003-36-5  01-2119454392-40-XXXX	Skin Irrit.2; H315 Skin Sens.1; H317 Aquatic Chronic2; H411	$\geq$ 5 - < 10
p-tert-butylphenyl 1-(2,3-epoxy)propyl ether	3101-60-8 221-453-2 01-2119959496-20-XXXX	Skin Sens.1; H317 Aquatic Chronic2; H411	$\geq$ 5 - < 10

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikafloor®-235 ESD (A)

Revision Date 07.09.2020

Version 1.0

Print Date 07.09.2020

benzyl alcohol	100-51-6 202-859-9 01-2119492630-38-XXXX	Acute Tox.4; H302 Acute Tox.4; H332 Eye Irrit.2; H319	>= 1 - < 2,5
----------------	--	---	--------------

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Allergic reactions  
Excessive lachrymation  
Erythema  
Dermatitis  
See Section 11 for more detailed information on health effects and symptoms.
- Risks : irritant effects  
sensitising effects  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikafloor®-235 ESD (A)

Revision Date 07.09.2020

Version 1.0

Print Date 07.09.2020

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

#### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Deny access to unprotected persons.

#### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For personal protection see section 8.

---

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikafloor®-235 ESD (A)

Revision Date 07.09.2020

Version 1.0

Print Date 07.09.2020

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

- Advice on safe handling : Do not breathe vapours or spray mist.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

#### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.
- Further information on storage stability : No decomposition if stored and applied as directed.

#### 7.3 Specific end use(s)

---

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

#### 8.2 Exposure controls

##### Personal protective equipment

- Eye protection : Safety glasses with side-shields conforming to EN166  
Eye wash bottle with pure water
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikafloor®-235 ESD (A)

Revision Date 07.09.2020

Version 1.0

Print Date 07.09.2020

facturer specifications.

Suitable for short time use or protection against splashes:  
Butyl rubber/nitrile rubber gloves (> 0,1 mm)

Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm),  
breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.

Respiratory protection : No special measures required.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: various
Odour	: epoxy-like
Odour Threshold	: No data available
pH	: Not applicable
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: > 101 °C Method: closed cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapour pressure	: 0,01 hPa 0,01 hPa
Relative vapour density	: No data available
Density	: ca. 1,68 g/cm <sup>3</sup> (20 °C)

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikafloor®-235 ESD (A)

Revision Date 07.09.2020

Version 1.0

Print Date 07.09.2020

---

Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	
	: No data available
Auto-ignition temperature	
	: No data available
	: No data available
Decomposition temperature	
	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: > 20,5 mm <sup>2</sup> /s (40 °C)
Explosive properties	
	: No data available
Oxidizing properties	
	: No data available

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

### 10.4 Conditions to avoid

Conditions to avoid : No data available

### 10.5 Incompatible materials

Materials to avoid : No data available

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikafloor®-235 ESD (A)

Revision Date 07.09.2020

Version 1.0

Print Date 07.09.2020

---

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

##### Acute toxicity

Not classified based on available information.

##### Components:

**reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq$  700):**

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20.000 mg/kg

##### **p-tert-butylphenyl 1-(2,3-epoxy)propyl ether:**

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 3.466 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rabbit): 6.000 mg/kg

##### **benzyl alcohol:**

Acute oral toxicity : LD50 Oral (Rat): 1.620 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4,178 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

##### **Skin corrosion/irritation**

Causes skin irritation.

##### **Serious eye damage/eye irritation**

Causes serious eye irritation.

##### **Respiratory or skin sensitisation**

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

##### **Germ cell mutagenicity**

Not classified based on available information.

##### **Carcinogenicity**

Not classified based on available information.

##### **Reproductive toxicity**

Not classified based on available information.

##### **STOT - single exposure**

Not classified based on available information.



# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikafloor®-235 ESD (A)

Revision Date 07.09.2020

Version 1.0

Print Date 07.09.2020

### STOT - repeated exposure

Not classified based on available information.

### Aspiration toxicity

Not classified based on available information.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

**reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq 700$ ):**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1,8 mg/l  
aquatic invertebrates : Exposure time: 48 h

#### **benzyl alcohol:**

Toxicity to fish : LC50 (Fish): > 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
aquatic invertebrates : Exposure time: 48 h

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Other adverse effects

#### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikafloor®-235 ESD (A)

Revision Date 07.09.2020

Version 1.0

Print Date 07.09.2020

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

- Product** : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.  
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.  
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- Contaminated packaging** : 15 01 10\* packaging containing residues of or contaminated by dangerous substances

---

### SECTION 14: Transport information

#### 14.1 UN number

- ADR** : UN 3082  
**IMDG** : UN 3082  
**IATA** : UN 3082

#### 14.2 UN proper shipping name

- ADR** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(epoxy resin)  
**IMDG** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(epoxy resin)  
**IATA** : Environmentally hazardous substance, liquid, n.o.s.  
(epoxy resin)

#### 14.3 Transport hazard class(es)

- ADR** : 9  
**IMDG** : 9  
**IATA** : 9

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikafloor®-235 ESD (A)

Revision Date 07.09.2020

Version 1.0

Print Date 07.09.2020

---

### 14.4 Packing group

#### ADR

Packing group : III  
Classification Code : M6  
Hazard Identification Number : 90  
Labels : 9  
Tunnel restriction code : (-)

#### IMDG

Packing group : III  
Labels : 9  
EmS Code : F-A, S-F

#### IATA (Cargo)

Packing instruction (cargo aircraft) : 964  
Packing instruction (LQ) : Y964  
Packing group : III  
Labels : Miscellaneous

#### IATA (Passenger)

Packing instruction (passenger aircraft) : 964  
Packing instruction (LQ) : Y964  
Packing group : III  
Labels : Miscellaneous

### 14.5 Environmental hazards

#### ADR

Environmentally hazardous : yes

#### IMDG

Marine pollutant : yes

#### IATA (Passenger)

Environmentally hazardous : yes

#### IATA (Cargo)

Environmentally hazardous : yes

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Country ZA 100000014968

11 / 14

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikafloor®-235 ESD (A)

Revision Date 07.09.2020

Version 1.0

Print Date 07.09.2020

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: Number on list 3
International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors	:	Not applicable
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	None of the components are listed (=> 0.1 %).
REACH - List of substances subject to authorisation (Annex XIV)	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
Regulation (EC) No 850/2004 on persistent organic pollutants	:	Not applicable
Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals	:	Not applicable
REACH Information:		All substances contained in our Products are - registered by our upstream suppliers, and/or - registered by us, and/or - excluded from the regulation, and/or - exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E2 ENVIRONMENTAL HAZARDS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)  
Volatile organic compounds (VOC) content: 3,63 %

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content:  
3,99 %, 67,1 g/l  
VOC content excluding water

### Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

---

## SECTION 16: Other information

### Full text of H-Statements

H302 : Harmful if swallowed.  
H315 : Causes skin irritation.

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and Hazardous Chemical Substance Regs. (GNR. 1179 of 25 August 1995)



## Sikafloor®-235 ESD (A)

Revision Date 07.09.2020

Version 1.0

Print Date 07.09.2020

- H317 : May cause an allergic skin reaction.  
H319 : Causes serious eye irritation.  
H332 : Harmful if inhaled.  
H411 : Toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

- Acute Tox. : Acute toxicity  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Eye Irrit. : Eye irritation  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitisation  
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road  
CAS : Chemical Abstracts Service  
DNEL : Derived no-effect level  
EC50 : Half maximal effective concentration  
GHS : Globally Harmonized System  
IATA : International Air Transport Association  
IMDG : International Maritime Code for Dangerous Goods  
LD50 : Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)  
LC50 : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)  
MARPOL : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978  
OEL : Occupational Exposure Limit  
PBT : Persistent, bioaccumulative and toxic  
PNEC : Predicted no effect concentration  
REACH : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency  
SVHC : Substances of Very High Concern  
vPvB : Very persistent and very bioaccumulative

### Classification of the mixture:

- Skin Irrit. 2 H315  
Eye Irrit. 2 H319  
Skin Sens. 1 H317  
Aquatic Chronic 2 H411

### Classification procedure:

- Calculation method  
Calculation method  
Calculation method  
Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

# SAFETY DATA SHEET

According to SANS 10234, SANS 10228, SANS 11014 and  
Hazardous Chemical Substance Regs. (GNR. 1179 of 25 Au-  
gust 1995)



## Sikafloor®-235 ESD (A)

Revision Date 07.09.2020

Version 1.0

Print Date 07.09.2020

---

ZA / EN